




flow, stop and go®



CACHÉ® CASCADE AERATORS

M24x1 (STD), aerated stream

Models with restrictor


Color code	Flow rate	M24x1 (STD)
	Z 7.5 -9.0 l/min at 3 bar	401202010
	A 13.5 - 15.0 l/min at 3 bar	401203010
	S 18.0 - 19.8 l/min at 3 bar	401204010
	B 22.8 - 25.2 l/min at 3 bar	401205010
	C 27.0 - 30.0 l/min at 3 bar	401206010
	D 34.8 - 37.8 l/min at 3 bar	401207010
	X 2.2 gpm max at 60 psi	401201010

PCA® models

Color code	Flow rate	M24x1 (STD)
	0.35 gpm max.	401268010
	0.5 gpm max.	401259010
	1.0 gpm max.	401258010
	1.2 gpm max.	401260010
	5.0 l/min	401251010
	1.5 gpm max.	401256010
	6.0 l/min	402252010
	1.75 gpm max.	401261010
	7.0 l/min	401255010
	2.0 gpm max.	401257010
	2.2 gpm max.	401253010
	8.0 l/min	401254010








flow, stop and go®



CACHÉ® CASCADE AERATORS

M24x1 (STD), aerated stream

PCA® Dual Core (DC) models

Color code	Flow rate	M24x1 (STD)
	1.0 gpm max.	401213010
	1.2 gpm max.	401214010
	1.5 gpm max.	401215010
	1.75 gpm max.	401217010
	2.1 gpm max.	401216010