



# DW-TYPE CHECK VALVES

**Features:** standard check valve for general applications

Nominal size: 10 – 20 mm  
 Installation: in or against direction of flow  
 Design: cartridge style

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW10/DN6	1.8 - 7.8	0.5 - 2.1	<a href="#">304010000</a>	10.1 mm
DW11/DN6	1.8 - 7.8	0.5 - 2.1	<a href="#">304011000</a>	11.1 mm
DW14/DN10	3.0 - 16.8	0.8 - 4.4	<a href="#">304014000</a>	14.4 mm
DW20/DN15-1T	4.8 - 48.0	1.3 - 12.7	<a href="#">304073000</a>	20.1 mm

**With glass fiber reinforced plunger for high back pressure loads (-GF):**

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW14/DN10-GF	3.0 - 16.8	0.8 - 4.4	<a href="#">304033000</a>	14.4 mm
DW15/DN10-GF	3.6 - 21.0	1.0 - 5.5	<a href="#">304043000</a>	15.1 mm

**With integrated pressure relief (-PR):**

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW14/DN10-AF-PR	3.0 - 16.8	0.8 - 4.4	<a href="#">304037000</a>	14.1 mm
DW14/DN10-PR	3.0 - 16.8	0.8 - 4.4	<a href="#">304032000</a>	14.4 mm
DW15/DN10-PR	3.6 - 21.0	1.0 - 5.5	<a href="#">304094000</a>	15.1 mm