



DW-TYPE CHECK VALVES

Features: standard check valve for general applications

Nominal size: 10 – 20 mm
 Installation: in or against direction of flow
 Design: cartridge style

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW10/DN6	1.8 - 7.8	0.5 - 2.1	304010000	10.1 mm
DW11/DN6	1.8 - 7.8	0.5 - 2.1	304011000	11.1 mm
DW14/DN10	3.0 - 16.8	0.8 - 4.4	304014000	14.4 mm
DW20/DN15-1T	4.8 - 48.0	1.3 - 12.7	304073000	20.1 mm

With glass fiber reinforced plunger for high back pressure loads (-GF):

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW14/DN10-GF	3.0 - 16.8	0.8 - 4.4	304033000	14.4 mm
DW15/DN10-GF	3.6 - 21.0	1.0 - 5.5	304043000	15.1 mm

With integrated pressure relief (-PR):

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW14/DN10-AF-PR	3.0 - 16.8	0.8 - 4.4	304037000	14.1 mm
DW14/DN10-PR	3.0 - 16.8	0.8 - 4.4	304032000	14.4 mm
DW15/DN10-PR	3.6 - 21.0	1.0 - 5.5	304094000	15.1 mm