



DW-TYPE CHECK VALVES

Feature: cylindrical check valve for general applications

Size: 10 – 20 mm | corresponding bore diameter: 10.1 - 20.1 mm

Installation: in or against direction of flow, axial retention required

Design: cartridge style

designation	bore diameter	recommended flow rate		sealing material	part number
		l/min	gpm		
DW10/DN6	10.1 mm	1.8 - 7.8	0.5 - 2.1	silicone	304010000
DW11/DN6	11.1 mm	1.8 - 7.8	0.5 - 2.1	silicone	304011000
DW14/DN10	14.4 mm	3.0 - 16.8	0.8 - 4.4	EPDM/TPE	304014000
DW20/DN15-1T	20.1 mm	4.8 - 48.0	1.3 - 12.7	silicone	304073000

With glass fiber reinforced plunger for high back pressure loads (-GF):

designation	bore diameter	recommended flow rate		sealing material	part number
		l/min	gpm		
DW15-GF-EPDM	15.1 mm	3.6 - 21.0	1.0 - 5.5	EPDM	304042000
DW14/DN10-GF	14.4 mm	1.8 - 7.8	0.5 - 2.1	silicone	304033000
DW15/DN10-GF	15.1 mm	3.6 - 21.0	1.0 - 5.5	silicone	304043000

With integrated pressure-relief (-PR):

designation	bore diameter	recommended flow rate		sealing material	part number
		l/min	gpm		
DW14/DN10-PR	14.4 mm	3.0 - 16.8	0.8 - 4.4	EPDM	304032000
DW15/DN10-PR	15.1 mm	3.6 - 21.0	1.0 - 5.5	EPDM	304094000