





















# NEOPERL® CACHÉ® CC SLC AERATORS

## All sizes, aerated stream

### Models with restrictor

Color code	Flow rate	M18.5×1 (TJ)	M21.5×1 (JR)	M24×1 (STD)
	Z 7.5 - 9.0 l/min at 3 bar	<a href="#">430202010</a>	<a href="#">420202010</a>	<a href="#">400202010</a>
	A 13.5 - 15.0 l/min at 3 bar	<a href="#">430203010</a>	<a href="#">420203010</a>	<a href="#">400203010</a>
	S 18.0 - 19.8 l/min at 3 bar			<a href="#">400202010</a>
	B 22.8 - 25.2 l/min at 3 bar	<a href="#">430205010</a>	<a href="#">420205010</a>	<a href="#">400205010</a>
	C 27.0 - 30.0 l/min at 3 bar			<a href="#">400206010</a>
	D 34.8 - 37.8 l/min at 3 bar			<a href="#">400207010</a>
	T 1.5 gpm max at 60 psi			<a href="#">400210010</a>
	X 2.2 gpm max at 60 psi	<a href="#">430201010</a>	<a href="#">420201010</a>	<a href="#">400201010</a>

### PCA® models

Color code	Flow rate	M18.5×1 (TJ)	M21.5×1 (JR)	M24×1 (STD)
	1.0 gpm max.			<a href="#">400258010</a>
	1.2 gpm max.			<a href="#">400260010</a>
	5.0 l/min	<a href="#">430251010</a>	<a href="#">420251010</a>	<a href="#">400251010</a>
	1.5 gpm max.	<a href="#">430256010</a>	<a href="#">420256010</a>	<a href="#">400256010</a>
	6.0 l/min			<a href="#">402252010</a>
	1.75 gpm max.	<a href="#">430261010</a>	<a href="#">420261010</a>	<a href="#">400261010</a>
	7.0 l/min	<a href="#">430255010</a>	<a href="#">420255010</a>	<a href="#">400255010</a>
	2.0 gpm max.	<a href="#">430257010</a>	<a href="#">420257010</a>	<a href="#">400257010</a>
	2.2 gpm max.	<a href="#">430253010</a>	<a href="#">420253010</a>	<a href="#">400253010</a>
	8.0 l/min	<a href="#">430254010</a>	<a href="#">420254010</a>	<a href="#">400254010</a>