



# PERLATOR® HC AERATORS

## STD size, aerated stream

### Models with restrictor

| Color code                                                                         |   | Flow rate                                          | STD insert                | Female M22×1              | Male M24×1                | Regular male 15/16"-27 | Regular female 55/64"-27 |
|------------------------------------------------------------------------------------|---|----------------------------------------------------|---------------------------|---------------------------|---------------------------|------------------------|--------------------------|
|    | Z | 7.5 - 9.0 l/min at 3 bar                           | <a href="#">402002000</a> | <a href="#">402002023</a> | <a href="#">402002033</a> | 402002613              | 402002623                |
|  | A | 13.5 - 15.0 l/min at 3 bar                         | <a href="#">402003000</a> | <a href="#">402003023</a> | <a href="#">402003033</a> | 402003613              | 402003623                |
|  | S | 18.0 - 19.8 l/min at 3 bar                         | <a href="#">402004000</a> | <a href="#">402004023</a> | <a href="#">402004033</a> | 402004613              | 402004623                |
|  | B | 22.8 - 25.2 l/min at 3 bar                         | <a href="#">402005000</a> | <a href="#">402005023</a> | <a href="#">402005033</a> | 402005613              | 402005623                |
|  | C | 27.0 - 30.0 l/min at 3 bar                         | <a href="#">402006000</a> | <a href="#">402006023</a> | <a href="#">402006033</a> | 402006613              | 402006623                |
|  | D | 34.8 - 37.8 l/min at 3 bar                         | <a href="#">402007000</a> | <a href="#">402007023</a> | <a href="#">402007033</a> | 402007613              | 402007623                |
|  |   | 1.0 gpm max. at 60 psi                             | <a href="#">403031000</a> | <a href="#">403031023</a> | <a href="#">403031033</a> | 403031613              | 403031623                |
|  | T | 1.5 gpm max at 60 psi                              | <a href="#">402010000</a> | <a href="#">402010023</a> | <a href="#">402010033</a> | 402010613              | 402010623                |
|  |   | 1.75 gpm max. at 60 psi                            | <a href="#">403039000</a> | <a href="#">403039023</a> | <a href="#">403039033</a> | 403039613              | 403039623                |
|  |   | 2.0 gpm max. at 60 psi                             | <a href="#">403033000</a> | <a href="#">403033023</a> | <a href="#">403033033</a> | 403033613              | 403033623                |
|  | X | 2.2 gpm max at 60 psi                              | <a href="#">402001000</a> | <a href="#">402001023</a> | <a href="#">402001033</a> | 402001613              | 402001623                |
|  |   | 3.0 gpm max. at 60 psi                             | <a href="#">403035000</a> | <a href="#">403035023</a> | <a href="#">403035033</a> | 403035613              | 403035623                |
|  |   | 3.5 gpm max. at 60 psi                             | <a href="#">403036000</a> | <a href="#">403036023</a> | <a href="#">403036033</a> | 403036613              | 403036623                |
|  | W | 4.0 gpm max. at 60 psi // 7.3 l/min at 1 bar       | <a href="#">403037000</a> | <a href="#">403037023</a> | <a href="#">403037033</a> | 403037613              | 403037623                |
|  | Y | 4.5 gpm max. at 60 psi // 8.0 l/min at 1 bar       | <a href="#">403038000</a> | <a href="#">403038023</a> | <a href="#">403038033</a> | 403038613              | 403038623                |
|  | V | optimal performance and aeration from 0.2 to 1 bar | <a href="#">403030000</a> | <a href="#">403030023</a> | <a href="#">403030033</a> | 403030613              | 403030623                |



flow, stop and go®



# PERLATOR® HC AERATORS

## STD size, aerated stream

### PCA® models

| Color code                                                                         | Flow rate     | STD insert                | Female M22×1              | Male M24×1                | Regular male 15/16"-27 | Regular female 55/64"-27 |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|------------------------|--------------------------|
|    | 1.0 gpm max.  | <a href="#">402058000</a> | <a href="#">402058023</a> | <a href="#">402058033</a> | 402058613              | 402058623                |
|  | 1.2 gpm max.  | <a href="#">402060000</a> | <a href="#">402060023</a> | <a href="#">402060033</a> | 402060613              | 402060623                |
|  | 5.0 l/min     | <a href="#">402051000</a> | <a href="#">402051023</a> | <a href="#">402051033</a> | 402051613              | 402051623                |
|  | 1.5 gpm max.  | <a href="#">402056000</a> | <a href="#">402056023</a> | <a href="#">402056033</a> | 402056613              | 402056623                |
|  | 6.0 l/min     | <a href="#">402052000</a> | <a href="#">402052023</a> | <a href="#">402052033</a> | 402052613              | 402052623                |
|  | 1.75 gpm max. | <a href="#">402061000</a> | <a href="#">402061023</a> | <a href="#">402061033</a> | 402061613              | 402061623                |
|  | 7.0 l/min     | <a href="#">402055000</a> | <a href="#">402055023</a> | <a href="#">402055033</a> | 402055613              | 402055623                |
|  | 2.0 gpm max.  | <a href="#">402057000</a> | <a href="#">402057023</a> | <a href="#">402057033</a> | 402057613              | 402057623                |
|  | 2.2 gpm max.  | <a href="#">402053000</a> | <a href="#">402053023</a> | <a href="#">402053033</a> | 402053613              | 402053623                |
|  | 8.0 l/min     | <a href="#">402054000</a> | <a href="#">402054023</a> | <a href="#">402054033</a> | 402054613              | 402054623                |



flow, stop and go®



# PERLATOR® HC AERATORS

## STD size, aerated stream

### PCA® Dual-Core (DC) models

| Color code                                                                         | Flow rate     |             | STD insert                | Female M22×1              | Male M24×1                |
|------------------------------------------------------------------------------------|---------------|-------------|---------------------------|---------------------------|---------------------------|
|    | 1.0 gpm max.  | (3.8 l/min) | <a href="#">402013000</a> | <a href="#">402013023</a> | <a href="#">402013033</a> |
|   | 1.2 gpm max.  | (4.5 l/min) | <a href="#">402014000</a> | <a href="#">402014023</a> | <a href="#">402014033</a> |
|  | 1.5 gpm max.  | (5.7 l/min) | <a href="#">402015000</a> | <a href="#">402015023</a> | <a href="#">402015033</a> |
|  | 1.75 gpm max. | (6.6 l/min) | <a href="#">402017000</a> | <a href="#">402017023</a> | <a href="#">402017033</a> |
|  | 2.1 gpm max.  | (8.0 l/min) | <a href="#">402016000</a> | <a href="#">402016023</a> | <a href="#">402016033</a> |



# PERLATOR® HC SSR AERATORS

## STD size, aerated stream

### Models with restrictor

| Color code                                                                         | Flow rate                    | STD insert                | Female M22×1              | Male M24×1                |
|------------------------------------------------------------------------------------|------------------------------|---------------------------|---------------------------|---------------------------|
|    | Z 7.5 - 9.0 l/min at 3 bar   | <a href="#">406002000</a> | <a href="#">406002023</a> | <a href="#">406002033</a> |
|    | A 13.5 - 15.0 l/min at 3 bar | <a href="#">406003000</a> | <a href="#">406003023</a> | <a href="#">406003033</a> |
|   | S 18.0 - 19.8 l/min at 3 bar | <a href="#">406004000</a> | <a href="#">406004023</a> | <a href="#">406004033</a> |
|  | B 22.8 - 25.2 l/min at 3 bar | <a href="#">406005000</a> | <a href="#">406005023</a> | <a href="#">406005033</a> |
|  | C 27.0 - 30.0 l/min at 3 bar | <a href="#">406006000</a> | <a href="#">406006023</a> | <a href="#">406006033</a> |
|  | D 34.8 - 37.8 l/min at 3 bar | <a href="#">406007000</a> | <a href="#">406007023</a> | <a href="#">406007033</a> |
|  | X 2.2 gpm max. at 60 psi     | <a href="#">406001000</a> | <a href="#">406001023</a> | <a href="#">406001033</a> |

### PCA® models

| Color code                                                                         | Flow rate     | STD insert                | Female M22×1              | Male M24×1                |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|
|  | 1.0 gpm max.  | <a href="#">406058000</a> | <a href="#">406058023</a> | <a href="#">406058033</a> |
|  | 1.2 gpm max.  | <a href="#">406060000</a> | <a href="#">406060023</a> | <a href="#">406060033</a> |
|  | 5.0 l/min     | <a href="#">406051000</a> | <a href="#">406051023</a> | <a href="#">406051033</a> |
|  | 1.5 gpm max.  | <a href="#">406056000</a> | <a href="#">406056023</a> | <a href="#">406056033</a> |
|  | 6.0 l/min     | <a href="#">406052000</a> | <a href="#">406052023</a> | <a href="#">406052033</a> |
|  | 1.75 gpm max. | <a href="#">406061000</a> | <a href="#">406061023</a> | <a href="#">406061033</a> |
|  | 7.0 l/min     | <a href="#">406055000</a> | <a href="#">406055023</a> | <a href="#">406055033</a> |
|  | 2.0 gpm max.  | <a href="#">406057000</a> | <a href="#">406057023</a> | <a href="#">406057033</a> |
|  | 2.2 gpm max.  | <a href="#">406053000</a> | <a href="#">406053023</a> | <a href="#">406053033</a> |
|  | 8.0 l/min     | <a href="#">406054000</a> | <a href="#">406054023</a> | <a href="#">406054033</a> |



flow, stop and go®



# PERLATOR® HC SSR AERATORS

## STD size, aerated stream

### PCA® Dual-Core (DC) models

| Color code                                                                         | Flow rate     |             | STD insert                | Female 22×1               | Male M24×1                |
|------------------------------------------------------------------------------------|---------------|-------------|---------------------------|---------------------------|---------------------------|
|    | 1.0 gpm max.  | (3.8 l/min) | <a href="#">406013000</a> | <a href="#">406013023</a> | <a href="#">406013033</a> |
|   | 1.2 gpm max.  | (4.5 l/min) | <a href="#">406014000</a> | <a href="#">406014023</a> | <a href="#">406014033</a> |
|  | 1.5 gpm max.  | (5.7 l/min) | <a href="#">406015000</a> | <a href="#">406015023</a> | <a href="#">406015033</a> |
|  | 1.75 gpm max. | (6.6 l/min) | <a href="#">406017000</a> | <a href="#">406017023</a> | <a href="#">406017033</a> |
|  | 2.1 gpm max.  | (8.0 l/min) | <a href="#">406016000</a> | <a href="#">406016023</a> | <a href="#">406016033</a> |



flow, stop and go®



# PERLATOR® HC AERATORS

## STD size, laminar stream

### Models with restrictor

| Color code                                                                         | Flow rate                                              | STD insert                | Female M22×1              | Male M24×1                | Regular male 15/16"-27 | Regular female 55/64"-27 |
|------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------|---------------------------|---------------------------|------------------------|--------------------------|
|    | Z 7.5 -9.0 l/min at 3 bar                              | <a href="#">402102000</a> | <a href="#">402102023</a> | <a href="#">402102033</a> | 402102613              | 402102623                |
|  | A 13.5 - 15.0 l/min at 3 bar                           | <a href="#">402103000</a> | <a href="#">402103023</a> | <a href="#">402103033</a> | 402103613              | 402103623                |
|  | S 18.0 - 19.8 l/min at 3 bar                           | <a href="#">402104000</a> | <a href="#">402104023</a> | <a href="#">402104033</a> | 402104613              | 402104623                |
|  | B 22.8 - 25.2 l/min at 3 bar                           | <a href="#">402105000</a> | <a href="#">402105023</a> | <a href="#">402105033</a> | 402105613              | 402105623                |
|  | C 27.0 - 30.0 l/min at 3 bar                           | <a href="#">402106000</a> | <a href="#">402106023</a> | <a href="#">402106033</a> | 402106613              | 402106623                |
|  | D 34.8 - 37.8 l/min at 3 bar                           | <a href="#">402107000</a> | <a href="#">402107023</a> | <a href="#">402107033</a> | 402107613              | 402107623                |
|  | T 1.5 gpm max at 60 psi                                | <a href="#">402110000</a> | <a href="#">402110023</a> | <a href="#">402110033</a> | 402110613              | 402110623                |
|  | X 2.2 gpm max at 60 psi                                | <a href="#">402101000</a> | <a href="#">402101023</a> | <a href="#">402101033</a> | 402101613              | 402101623                |
|  | max. flow with minimum restriction 20 l/min at 0.3 bar | <a href="#">402100000</a> | <a href="#">402100023</a> | <a href="#">402100033</a> | 402100613              | 402100623                |



flow, stop and go®




# PERLATOR® HC AERATORS

## STD size, laminar stream

### PCA® models

| Color code                                                                         | Flow rate     | STD insert                | Female M22×1              | Male M24×1                | Regular male 15/16"-27 | Regular female 55/64"-27 |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|------------------------|--------------------------|
|    | 0.5 gpm max.  | <a href="#">402159000</a> | <a href="#">402159023</a> | <a href="#">402159033</a> | 402159613              | 402159623                |
|   | 1.0 gpm max.  | <a href="#">402158000</a> | <a href="#">402158023</a> | <a href="#">402158033</a> | 402158613              | 402158623                |
|  | 1.2 gpm max.  | <a href="#">402160000</a> | <a href="#">402160023</a> | <a href="#">402160033</a> | 402160613              | 402160623                |
|  | 5.0 l/min     | <a href="#">402151000</a> | <a href="#">402151023</a> | <a href="#">402151033</a> | 402151613              | 402151623                |
|  | 1.5 gpm max.  | <a href="#">402156000</a> | <a href="#">402156023</a> | <a href="#">402156033</a> | 402156613              | 402156623                |
|  | 6.0 l/min     | <a href="#">402152000</a> | <a href="#">402152023</a> | <a href="#">402152033</a> | 402152613              | 402152623                |
|  | 1.75 gpm max. | <a href="#">402161000</a> | <a href="#">402161023</a> | <a href="#">402161033</a> | 402161613              | 402161623                |
|  | 7.0 l/min     | <a href="#">402155000</a> | <a href="#">402155023</a> | <a href="#">402155033</a> | 402155613              | 402155623                |
|  | 2.0 gpm max.  | <a href="#">402157000</a> | <a href="#">402157023</a> | <a href="#">402157033</a> | 402157613              | 402157623                |
|  | 2.2 gpm max.  | <a href="#">402153000</a> | <a href="#">402153023</a> | <a href="#">402153033</a> | 402153613              | 402153623                |
|  | 8.0 l/min     | <a href="#">402154000</a> | <a href="#">402154023</a> | <a href="#">402154033</a> | 402154613              | 402154623                |



# PERLATOR® HC AERATORS

## TT size, aerated stream

### Models with restrictor

| Color code                                                                         | Flow rate                                            | TT insert                 | Female M16×1              | Male M18×1                | Female 3/8"               |
|------------------------------------------------------------------------------------|------------------------------------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
|    | 1.0 gpm max at 60 psi                                | <a href="#">443031000</a> | <a href="#">443031023</a> | <a href="#">443031033</a> | <a href="#">443031043</a> |
|    | 1.5 gpm max at 60 psi                                | <a href="#">443032000</a> | <a href="#">443032023</a> | <a href="#">443032033</a> | <a href="#">443032043</a> |
|   | X 2.2 gpm max at 60 psi                              | <a href="#">443034000</a> | <a href="#">443034023</a> | <a href="#">443034033</a> | <a href="#">443034043</a> |
|  | V optimal performance and aeration from 0.2 to 1 bar | <a href="#">443030000</a> | <a href="#">443030023</a> | <a href="#">443030033</a> | <a href="#">443030043</a> |

### PCA® models

| Color code                                                                         | Flow rate     | TT insert                 | Female M16×1              | Male M18×1                | Female 3/8"               |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|---------------------------|
|  | 1.0 gpm max.  | <a href="#">443058000</a> | <a href="#">443058023</a> | <a href="#">443058033</a> | <a href="#">443058043</a> |
|  | 1.2 gpm max.  | <a href="#">443060000</a> | <a href="#">443060023</a> | <a href="#">443060033</a> | <a href="#">443060043</a> |
|  | 5.0 l/min     | <a href="#">443051000</a> | <a href="#">443051023</a> | <a href="#">443051033</a> | <a href="#">443051043</a> |
|  | 1.5 gpm max.  | <a href="#">443056000</a> | <a href="#">443056023</a> | <a href="#">443056033</a> | <a href="#">443056043</a> |
|  | 1.75 gpm max. | <a href="#">443061000</a> | <a href="#">443061023</a> | <a href="#">443061033</a> | <a href="#">443061043</a> |
|  | 7.0 l/min     | <a href="#">443055000</a> | <a href="#">443055023</a> | <a href="#">443055033</a> | <a href="#">443055043</a> |
|  | 2.0 gpm max.  | <a href="#">443057000</a> | <a href="#">443057023</a> | <a href="#">443057033</a> | <a href="#">443057043</a> |
|  | 2.2 gpm max.  | <a href="#">443053000</a> | <a href="#">443053023</a> | <a href="#">443053033</a> | <a href="#">443053043</a> |
|  | 8.0 l/min     | <a href="#">443054000</a> | <a href="#">443054023</a> | <a href="#">443054033</a> | <a href="#">443054043</a> |





# PERLATOR® HC AERATORS

## TT size, laminar stream

### Models with restrictor

| Color code                                                                         | Flow rate                               | TT insert                 | Female M16×1              | Male M18×1                | Female 3/8"               |
|------------------------------------------------------------------------------------|-----------------------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
|    | 1.5 gpm max at 60 psi                   | <a href="#">443132000</a> | <a href="#">443132023</a> | <a href="#">443132033</a> | <a href="#">443132043</a> |
|    | 2.2 gpm max at 60 psi                   | <a href="#">443134000</a> | <a href="#">443134023</a> | <a href="#">443134033</a> | <a href="#">443134043</a> |
|   | v optimal performance from 0.2 to 1 bar | <a href="#">443130000</a> | <a href="#">443130023</a> | <a href="#">443130033</a> | <a href="#">443130043</a> |
|  | max. flow with minimal restriction      | <a href="#">442100000</a> | <a href="#">442100023</a> | <a href="#">442100033</a> | <a href="#">442100043</a> |

### PCA® models

| Color code                                                                         | Flow rate     | TT insert                 | Female M16×1              | Male M18×1                | Female 3/8"               |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|---------------------------|
|  | 1.0 gpm max.  | <a href="#">443158000</a> | <a href="#">443158023</a> | <a href="#">443158033</a> | <a href="#">443158043</a> |
|  | 1.2 gpm max.  | <a href="#">443160000</a> | <a href="#">443160023</a> | <a href="#">443160033</a> | <a href="#">443160043</a> |
|  | 5.0 l/min     | <a href="#">443151000</a> | <a href="#">443151023</a> | <a href="#">443151033</a> | <a href="#">443151043</a> |
|  | 1.5 gpm max.  | <a href="#">443156000</a> | <a href="#">443156023</a> | <a href="#">443156033</a> | <a href="#">443156043</a> |
|  | 1.75 gpm max. | <a href="#">443161000</a> | <a href="#">443161023</a> | <a href="#">443161033</a> | <a href="#">443161043</a> |
|  | 7.0 l/min     | <a href="#">443155000</a> | <a href="#">443155023</a> | <a href="#">443155033</a> | <a href="#">443155043</a> |
|  | 2.0 gpm max.  | <a href="#">443157000</a> | <a href="#">443157023</a> | <a href="#">443157033</a> | <a href="#">443157043</a> |
|  | 2.2 gpm max.  | <a href="#">443153000</a> | <a href="#">443153023</a> | <a href="#">443153033</a> | <a href="#">443153043</a> |
|  | 8.0 l/min     | <a href="#">443154000</a> | <a href="#">443154023</a> | <a href="#">443154033</a> | <a href="#">443154043</a> |



# PERLATOR® HC AERATORS

## TJ size, aerated stream

### Models with restrictor

| Color code                                                                         | Flow rate                                            | TJ insert                 | Female M19×1              | Male M20×1                |
|------------------------------------------------------------------------------------|------------------------------------------------------|---------------------------|---------------------------|---------------------------|
|    | Z 7.5 - 9.0 l/min at 3 bar                           | <a href="#">432002000</a> | <a href="#">432002023</a> | <a href="#">432002033</a> |
|    | A 13.5 - 15.0 l/min at 3 bar                         | <a href="#">432003000</a> | <a href="#">432003023</a> | <a href="#">432003033</a> |
|   | B 22.8 - 25.2 l/min at 3 bar                         | <a href="#">432005000</a> | <a href="#">432005023</a> | <a href="#">432005033</a> |
|  | X 2.2 gpm max at 60 psi                              | <a href="#">432001000</a> | <a href="#">432001023</a> | <a href="#">432001033</a> |
|  | V optimal performance and aeration from 0.2 to 1 bar | <a href="#">433030000</a> | <a href="#">433030023</a> | <a href="#">433030033</a> |

### PCA® models

| Color code                                                                         | Flow rate     | TJ insert                 | Female M19×1              | Male M20×1                |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|
|  | 0.5 gpm max.  | <a href="#">432059000</a> | <a href="#">432059023</a> | <a href="#">432059033</a> |
|  | 1.0 gpm max.  | <a href="#">432058000</a> | <a href="#">432058023</a> | <a href="#">432058033</a> |
|  | 1.2 gpm max.  | <a href="#">432060000</a> | <a href="#">432060023</a> | <a href="#">432060033</a> |
|  | 5.0 l/min     | <a href="#">432051000</a> | <a href="#">432051023</a> | <a href="#">432051033</a> |
|  | 1.5 gpm max.  | <a href="#">432056000</a> | <a href="#">432056023</a> | <a href="#">432056033</a> |
|  | 1.75 gpm max. | <a href="#">432061000</a> | <a href="#">432061023</a> | <a href="#">432061033</a> |
|  | 7.0 l/min     | <a href="#">432055000</a> | <a href="#">432055023</a> | <a href="#">432055033</a> |
|  | 2.0 gpm max.  | <a href="#">432057000</a> | <a href="#">432057023</a> | <a href="#">432057033</a> |
|  | 2.2 gpm max.  | <a href="#">432053000</a> | <a href="#">432053023</a> | <a href="#">432053033</a> |
|  | 8.0 l/min     | <a href="#">432054000</a> | <a href="#">432054023</a> | <a href="#">432054033</a> |



flow, stop and go®



# PERLATOR® HC AERATORS

## TJ size, aerated stream

### PCA® Dual-Core (DC) models

| Color code                                                                         | Flow rate     |             | STD insert                | Female M19×1              | Male M20×1                |
|------------------------------------------------------------------------------------|---------------|-------------|---------------------------|---------------------------|---------------------------|
|    | 1.0 gpm max.  | (3.8 l/min) | <a href="#">433013000</a> | <a href="#">433013023</a> | <a href="#">433013033</a> |
|   | 1.2 gpm max.  | (4.5 l/min) | <a href="#">433014000</a> | <a href="#">433014023</a> | <a href="#">433014033</a> |
|  | 1.5 gpm max.  | (5.7 l/min) | <a href="#">433015000</a> | <a href="#">433015023</a> | <a href="#">433015033</a> |
|  | 1.75 gpm max. | (6.6 l/min) | <a href="#">433017000</a> | <a href="#">433017023</a> | <a href="#">433017033</a> |
|  | 2.1 gpm max.  | (8.0 l/min) | <a href="#">433016000</a> | <a href="#">433016023</a> | <a href="#">433016033</a> |



flow, stop and go®



# PERLATOR® HC SSR AERATORS

## TJ size, aerated stream

### Models with restrictor

| Color code                                                                         | Flow rate                    | TJ insert                 | Female M19×1              | Male M20×1                |
|------------------------------------------------------------------------------------|------------------------------|---------------------------|---------------------------|---------------------------|
|    | Z 7.5 - 9.0 l/min at 3 bar   | <a href="#">436002000</a> | <a href="#">436002023</a> | <a href="#">436002033</a> |
|    | A 13.5 - 15.0 l/min at 3 bar | <a href="#">436003000</a> | <a href="#">436003023</a> | <a href="#">436003033</a> |
|   | B 22.8 - 25.2 l/min at 3 bar | <a href="#">436005000</a> | <a href="#">436005023</a> | <a href="#">436005033</a> |
|  | X 2.2 gpm max at 60 psi      | <a href="#">436001000</a> | <a href="#">436001023</a> | <a href="#">436001033</a> |

### PCA® models

| Color code                                                                         | Flow rate     | TJ insert                 | Female M19×1              | Male M20×1                |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|
|  | 5.0 l/min     | <a href="#">436051000</a> | <a href="#">436051023</a> | <a href="#">436051033</a> |
|  | 1.5 gpm max.  | <a href="#">436056000</a> | <a href="#">436056023</a> | <a href="#">436056033</a> |
|  | 1.75 gpm max. | <a href="#">436061000</a> | <a href="#">436061023</a> | <a href="#">436061033</a> |
|  | 7.0 l/min     | <a href="#">436055000</a> | <a href="#">436055023</a> | <a href="#">436055033</a> |
|  | 2.0 gpm max.  | <a href="#">436057000</a> | <a href="#">436057023</a> | <a href="#">436057033</a> |
|  | 2.2 gpm max.  | <a href="#">436053000</a> | <a href="#">436053023</a> | <a href="#">436053033</a> |
|  | 8.0 l/min     | <a href="#">436054000</a> | <a href="#">436054023</a> | <a href="#">436054033</a> |



flow, stop and go®



# PERLATOR® HC SSR AERATORS

## TJ size, aerated stream

### PCA® Dual-Core (DC) models

| Color code                                                                         | Flow rate     |             | TJ insert                 | Female M19x1              | Male M20x1                |
|------------------------------------------------------------------------------------|---------------|-------------|---------------------------|---------------------------|---------------------------|
|    | 1.0 gpm max.  | (3.8 l/min) | <a href="#">436013000</a> | <a href="#">436013023</a> | <a href="#">436013033</a> |
|   | 1.2 gpm max.  | (4.5 l/min) | <a href="#">436014000</a> | <a href="#">436014023</a> | <a href="#">436014033</a> |
|  | 1.5 gpm max.  | (5.7 l/min) | <a href="#">436015000</a> | <a href="#">436015023</a> | <a href="#">436015033</a> |
|  | 1.75 gpm max. | (6.6 l/min) | <a href="#">436017000</a> | <a href="#">436017023</a> | <a href="#">436017033</a> |
|  | 2.1 gpm max.  | (8.0 l/min) | <a href="#">436016000</a> | <a href="#">436016023</a> | <a href="#">436016033</a> |



# PERLATOR® HC AERATORS


## JR size, aerated stream

### Models with restrictor

| Color code                                                                           | Flow rate                                             | JR insert                 | Fem. 3/4"-27<br>UNS-2B    | Male 13/16"-<br>27 UNS-2A |
|--------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------|---------------------------|---------------------------|
|      | 1.0 gpm max. at 60 psi                                | <a href="#">423031000</a> | <a href="#">423031033</a> | <a href="#">423031023</a> |
|      | 1.5 gpm max at 60 psi                                 | <a href="#">423032000</a> | <a href="#">423032033</a> | <a href="#">423032023</a> |
|    | 1.75 gpm max. at 60 psi                               | <a href="#">423039000</a> | <a href="#">423039033</a> | <a href="#">423039023</a> |
|    | 2.0 gpm max. at 60 psi                                | <a href="#">423033000</a> | <a href="#">423033033</a> | <a href="#">423033023</a> |
|    | 2.2 gpm max at 60 psi                                 | <a href="#">423034000</a> | <a href="#">423034033</a> | <a href="#">423034023</a> |
|  W | 4.0 gpm max. at 60 psi //<br>7.3 l/min at 1 bar       | <a href="#">423037000</a> | <a href="#">423037033</a> | <a href="#">423037023</a> |
|  Y | 4.5 gpm max. at 60 psi //<br>8.0 l/min at 1 bar       | <a href="#">423038000</a> | <a href="#">423038033</a> | <a href="#">423038023</a> |
|  V | optimal performance and<br>aeration from 0.2 to 1 bar | <a href="#">423030000</a> | <a href="#">423030033</a> | <a href="#">423030023</a> |

### PCA® models

| Color code                                                                         | Flow rate     | JR insert                 | Fem. 3/4"-27<br>UNS-2B    | Male 13/16"-<br>27 UNS-2A |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|
|  | 0.5 gpm max.  | <a href="#">422059000</a> | <a href="#">422059033</a> | <a href="#">422059023</a> |
|  | 1.0 gpm max.  | <a href="#">423058000</a> | <a href="#">423058033</a> | <a href="#">423058023</a> |
|  | 1.2 gpm max.  | <a href="#">423060000</a> | <a href="#">423060033</a> | <a href="#">423060023</a> |
|  | 1.5 gpm max.  | <a href="#">423056000</a> | <a href="#">423056033</a> | <a href="#">423056023</a> |
|  | 1.75 gpm max. | <a href="#">423061000</a> | <a href="#">423061033</a> | <a href="#">423061023</a> |
|  | 2.0 gpm max.  | <a href="#">423057000</a> | <a href="#">423057033</a> | <a href="#">423057023</a> |
|  | 2.2 gpm max.  | <a href="#">423053000</a> | <a href="#">423053033</a> | <a href="#">423053023</a> |



# PERLATOR® HC AERATORS

## JR size, laminar stream

### Models with restrictor

| Color code                                                                         | Flow rate                                         | JR insert                 | Fem. 3/4"-27<br>UNS-2B    | Male 13/16"-<br>27 UNS-2A |
|------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------|---------------------------|---------------------------|
|    | 1.0 gpm max. at 60 psi                            | <a href="#">423131000</a> | <a href="#">423131033</a> | <a href="#">423131023</a> |
|   | 1.5 gpm max at 60 psi                             | <a href="#">423132000</a> | <a href="#">423132033</a> | <a href="#">423132023</a> |
|  | 1.75 gpm max. at 60 psi                           | <a href="#">423139000</a> | <a href="#">423139033</a> | <a href="#">423139023</a> |
|  | 2.0 gpm max. at 60 psi                            | <a href="#">423133000</a> | <a href="#">423133033</a> | <a href="#">423133023</a> |
|  | 2.2 gpm max at 60 psi                             | <a href="#">423134000</a> | <a href="#">423134033</a> | <a href="#">423134023</a> |
|  | W 4.0 gpm max. at 60 psi //<br>7.3 l/min at 1 bar | <a href="#">423137000</a> | <a href="#">423137033</a> | <a href="#">423137023</a> |
|  | Y 4.5 gpm max. at 60 psi //<br>8.0 l/min at 1 bar | <a href="#">423138000</a> | <a href="#">423138033</a> | <a href="#">423138023</a> |
|  | V optimal performance<br>from 0.2 to 1 bar        | <a href="#">423130000</a> | <a href="#">423130033</a> | <a href="#">423130023</a> |

### PCA® models

| Color code                                                                         | Flow rate     | JR insert                 | Fem. 3/4"-27<br>UNS-2B    | Male 13/16"-<br>27 UNS-2A |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|
|  | 0.5 gpm max.  | <a href="#">423159000</a> | <a href="#">423159033</a> | <a href="#">423159023</a> |
|  | 1.0 gpm max.  | <a href="#">423158000</a> | <a href="#">423158033</a> | <a href="#">423158023</a> |
|  | 1.2 gpm max.  | <a href="#">423160000</a> | <a href="#">423160033</a> | <a href="#">423160023</a> |
|  | 1.5 gpm max.  | <a href="#">423156000</a> | <a href="#">423156033</a> | <a href="#">423156023</a> |
|  | 1.75 gpm max. | <a href="#">423161000</a> | <a href="#">423161033</a> | <a href="#">423161023</a> |
|  | 2.0 gpm max.  | <a href="#">423157000</a> | <a href="#">423157033</a> | <a href="#">423157023</a> |
|  | 2.2 gpm max.  | <a href="#">423153000</a> | <a href="#">423153033</a> | <a href="#">423153023</a> |



flow, stop and go®



# PERLATOR® HC AERATORS

## TF size, aerated stream

### Models with restrictor

| Color code                                                                         | Flow rate                                            | TF insert                 | Male M28×1                |
|------------------------------------------------------------------------------------|------------------------------------------------------|---------------------------|---------------------------|
|    | B 22.8 - 25.2 l/min at 3 bar                         | <a href="#">412005000</a> | <a href="#">412005093</a> |
|    | C 27.0 - 30.0 l/min at 3 bar                         | <a href="#">412006000</a> | <a href="#">412006093</a> |
|   | D 34.8 - 37.8 l/min at 3 bar                         | <a href="#">412007000</a> | <a href="#">412007093</a> |
|  | G 60.0 - 70.0 l/min at 1 bar                         | <a href="#">412008000</a> | <a href="#">412008093</a> |
|  | M 60.0 - 70.0 l/min at 3 bar                         | <a href="#">412009000</a> | <a href="#">412009093</a> |
|  | V optimal performance and aeration from 0.2 to 1 bar | <a href="#">413030000</a> | <a href="#">413030093</a> |





# PERLATOR® HC AC AERATORS

## STD size, aerated stream

### Models with restrictor

| Color code                                                                        | Flow rate                                              | STD insert                | Female M22×1              | Male M24×1                |
|-----------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------|---------------------------|---------------------------|
|   | Z 7.5 - 9.0 l/min at 3 bar                             | <a href="#">402402000</a> | <a href="#">402402023</a> | <a href="#">402402033</a> |
|   | A 13.5 - 15.0 l/min at 3 bar                           | <a href="#">402403000</a> | <a href="#">402403023</a> | <a href="#">402403033</a> |
|  | V optimal performance and aeration from 0.2 to 1.0 bar | <a href="#">403430000</a> | <a href="#">403430023</a> | <a href="#">403430033</a> |

### PCA® models

| Color code                                                                         | Flow rate     | STD insert                | Female M22×1              | Male M24×1                |
|------------------------------------------------------------------------------------|---------------|---------------------------|---------------------------|---------------------------|
|  | 5.0 l/min     | <a href="#">402451000</a> | <a href="#">402451023</a> | <a href="#">402451033</a> |
|  | 1.5 gpm max.  | <a href="#">402456000</a> | <a href="#">402456023</a> | <a href="#">402456033</a> |
|  | 1.75 gpm max. | <a href="#">402461000</a> | <a href="#">402461023</a> | <a href="#">402461033</a> |
|  | 7.0 l/min     | <a href="#">402455000</a> | <a href="#">402455023</a> | <a href="#">402455033</a> |
|  | 2.0 gpm max.  | <a href="#">402457000</a> | <a href="#">402457023</a> | <a href="#">402457033</a> |
|  | 2.2 gpm max.  | <a href="#">402453000</a> | <a href="#">402453023</a> | <a href="#">402453033</a> |