



SLIM® AIR AERATORS

All sizes, aerated stream with enhanced stream technology

PCA® Dual-Core (DC) models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	Male 15/16"-27 UNS-2A (STD) with Coin Slot	M24x1 (STD)	M24x1 (STD) with Coin Slot
	1.0 gpm max.	4083131505	4520130505	4083130105	4520130005
	1.2 gpm max.	4083141505	4520140505	4083140105	4520140005
	1.5 gpm max.	4083151505	4520150505	4083150105	4520150005
	1.75 gpm max.	4083171505	4520170505	4083170105	4520170005
	2.1 gpm max.	4083161505	4520160505	4083160105	4520160005

V+ model

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	Male 15/16"-27 UNS-2A (STD) with Coin Slot	M24x1 (STD)	M24x1 (STD) with Coin Slot
	V V+ optimal performance and aeration from 0.5 to 1.5 bar	4083311505	4530310505	4083310105	4530310005



flow, stop and go®



SLIM® AIR HC AERATORS

All sizes, aerated stream

Models with restrictor

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	✓ optimal performance and aeration from 0.2 to 1 bar	<u>408330150</u>	<u>408330010</u>

PCA® models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	1.0 gpm max.	<u>408358150</u>	<u>408358010</u>
	1.2 gpm max.	<u>408360150</u>	<u>408360010</u>
	5.0 l/min	<u>408351150</u>	<u>408351010</u>
	1.5 gpm max.	<u>408356150</u>	<u>408356010</u>
	7.0 l/min	<u>408355150</u>	<u>408355010</u>
	2.2 gpm max.	<u>408353150</u>	<u>408353010</u>
	8.0 l/min	<u>408354150</u>	<u>408354010</u>



flow, stop and go®



SLIM® AIR HC SSR AERATORS

All sizes, aerated stream

Models with restrictor

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	✓ optimal performance and aeration from 0.2 to 1 bar	<u>408030150</u>	<u>408030010</u>

PCA® models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	1.2 gpm max.	<u>408060150</u>	<u>408060010</u>
	5.0 l/min	<u>408051150</u>	<u>408051010</u>
	1.5 gpm max.	<u>408056150</u>	<u>408056010</u>
	7.0 l/min	<u>408055150</u>	<u>408055010</u>
	2.0 gpm max.	<u>408057150</u>	<u>408057010</u>
	2.2 gpm max.	<u>408053150</u>	<u>408053010</u>
	8.0 l/min	<u>408054150</u>	<u>408054010</u>



flow, stop and go®



SLIM® AIR HC SSR AERATORS

All sizes, aerated stream

PCA® Dual-Core (DC) models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	1.2 gpm max.	408014150	408014010
	1.5 gpm max.	408015150	408015010
	1.75 gpm max.	408017150	408017010
	2.1 gpm max.	408016150	408016010



flow, stop and go®



SLIM® AIR CC SLC® AERATORS

All sizes, aerated stream

Models with restrictor

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	v optimal performance and aeration from 0.2 to 1 bar	<u>408430150</u>	<u>408430010</u>

PCA® models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	1.2 gpm max.	<u>408460150</u>	<u>408460010</u>
	5.0 l/min	<u>408451150</u>	<u>408451010</u>
	1.5 gpm max.	<u>408456150</u>	<u>408456010</u>
	7.0 l/min	<u>408455150</u>	<u>408455010</u>
	2.2 gpm max.	<u>408453150</u>	<u>408453010</u>
	8.0 l/min	<u>408454150</u>	<u>408454010</u>



flow, stop and go®



SLIM® AIR CC SLC® AERATORS

All sizes, aerated stream

PCA® Dual-Core (DC) models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	1.0 gpm max.	408413150	408413010
	1.2 gpm max.	408414150	408414010
	1.5 gpm max.	408415150	408415010
	1.75 gpm max.	408417150	408417010
	2.1 gpm max.	408416150	408416010



flow, stop and go®



SLIM® AIR CC SLC® SSR AERATORS

All sizes, aerated stream

Models with restrictor

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	✓ optimal performance and aeration from 0.2 to 1 bar	<u>408130150</u>	<u>408130010</u>

PCA® models

Color code	Flow rate	Male 15/16"-27 UNS-2A (STD)	M24×1 (STD)
	1.2 gpm max.	<u>408160150</u>	<u>408160010</u>
	5.0 l/min	<u>408151150</u>	<u>408151010</u>
	1.5 gpm max.	<u>408156150</u>	<u>408156010</u>
	7.0 l/min	<u>408155150</u>	<u>408155010</u>
	2.0 gpm max.	<u>408157150</u>	<u>408157010</u>
	2.2 gpm max.	<u>408153150</u>	<u>408153010</u>
	8.0 l/min	<u>408154150</u>	<u>408154010</u>



flow, stop and go®



SLIM[®] CC SLC[®] AERATORS

All sizes, laminar stream

PCA[®] Dual-Core (DC) models

Color code	Flow rate	M24×1 (STD)
	1.2 gpm max.	<u>408260010</u>
	1.5 gpm max.	<u>408256010</u>
	2.2 gpm max.	<u>408253010</u>