




flow, stop and go®










SLIM AIR HC AERATORS

All sizes, aerated stream

Models with restrictor

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|--|--|--------------------------------|------------------|
|  | √ optimal performance and aeration from 0.2 to 1 bar | <u>408330150</u> | <u>408330010</u> |

PCA® models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|--|--------------|--------------------------------|------------------|
|  | 1.0 gpm max. | <u>408358150</u> | <u>408358010</u> |
|  | 1.2 gpm max. | <u>408360150</u> | <u>408360010</u> |
|  | 5.0 l/min | <u>408351150</u> | <u>408351010</u> |
|  | 1.5 gpm max. | <u>408356150</u> | <u>408356010</u> |
|  | 7.0 l/min | <u>408355150</u> | <u>408355010</u> |
|  | 2.2 gpm max. | <u>408353150</u> | <u>408353010</u> |
|  | 8.0 l/min | <u>408354150</u> | <u>408354010</u> |








flow, stop and go®



SLIM AIR HC AERATORS

All sizes, aerated stream

PCA® Dual-Core (DC) models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|--|---------------|----------------------------------|----------------------------------|
|  | 1.0 gpm max. | <u>408313150</u> | <u>408313010</u> |
|  | 1.2 gpm max. | <u>408314150</u> | <u>408314010</u> |
|  | 1.5 gpm max. | <u>408315150</u> | <u>408315010</u> |
|  | 1.75 gpm max. | <u>408317150</u> | <u>408317010</u> |
|  | 2.1 gpm max. | <u>408316150</u> | <u>408316010</u> |



flow, stop and go®



SLIM AIR HC SSR AERATORS

All sizes, aerated stream

Models with restrictor

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|------------|--|--------------------------------|------------------|
| | √ optimal performance and aeration from 0.2 to 1 bar | <u>408030150</u> | <u>408030010</u> |

PCA® models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|------------|--------------|--------------------------------|------------------|
| | 1.2 gpm max. | <u>408060150</u> | <u>408060010</u> |
| | 5.0 l/min | <u>408051150</u> | <u>408051010</u> |
| | 1.5 gpm max. | <u>408056150</u> | <u>408056010</u> |
| | 7.0 l/min | <u>408055150</u> | <u>408055010</u> |
| | 2.0 gpm max. | <u>408057150</u> | <u>408057010</u> |
| | 2.2 gpm max. | <u>408053150</u> | <u>408053010</u> |
| | 8.0 l/min | <u>408054150</u> | <u>408054010</u> |








flow, stop and go®



SLIM AIR HC SSR AERATORS

All sizes, aerated stream

PCA® Dual-Core (DC) models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|--|---------------|----------------------------------|----------------------------------|
|  | 1.0 gpm max. | <u>408013150</u> | <u>408013010</u> |
|  | 1.2 gpm max. | <u>408014150</u> | <u>408014010</u> |
|  | 1.5 gpm max. | <u>408015150</u> | <u>408015010</u> |
|  | 1.75 gpm max. | <u>408017150</u> | <u>408017010</u> |
|  | 2.1 gpm max. | <u>408016150</u> | <u>408016010</u> |



flow, stop and go®



SLIM AIR CC SLC AERATORS

All sizes, aerated stream

Models with restrictor

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|------------|--|--------------------------------|------------------|
| | √ optimal performance and aeration from 0.2 to 1 bar | <u>408430150</u> | <u>408430010</u> |

PCA® models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|------------|--------------|--------------------------------|------------------|
| | 1.2 gpm max. | <u>408460150</u> | <u>408460010</u> |
| | 5.0 l/min | <u>408451150</u> | <u>408451010</u> |
| | 1.5 gpm max. | <u>408456150</u> | <u>408456010</u> |
| | 7.0 l/min | <u>408455150</u> | <u>408455010</u> |
| | 2.2 gpm max. | <u>408453150</u> | <u>408453010</u> |
| | 8.0 l/min | <u>408454150</u> | <u>408454010</u> |








flow, stop and go®



SLIM AIR CC SLC AERATORS

All sizes, aerated stream

PCA® Dual-Core (DC) models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|--|---------------|--------------------------------|---------------------------|
|  | 1.0 gpm max. | 408413150 | 408413010 |
|  | 1.2 gpm max. | 408414150 | 408414010 |
|  | 1.5 gpm max. | 408415150 | 408415010 |
|  | 1.75 gpm max. | 408417150 | 408417010 |
|  | 2.1 gpm max. | 408416150 | 408416010 |



flow, stop and go®



SLIM AIR CC SLC SSR AERATORS

All sizes, aerated stream

Models with restrictor

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|------------|--|--------------------------------|------------------|
| | √ optimal performance and aeration from 0.2 to 1 bar | <u>408130150</u> | <u>408130010</u> |

PCA® models

| Color code | Flow rate | Male 15/16"-27 UNS-2A (STD) | M24x1 (STD) |
|------------|--------------|--------------------------------|------------------|
| | 1.2 gpm max. | <u>408160150</u> | <u>408160010</u> |
| | 5.0 l/min | <u>408151150</u> | <u>408151010</u> |
| | 1.5 gpm max. | <u>408156150</u> | <u>408156010</u> |
| | 7.0 l/min | <u>408155150</u> | <u>408155010</u> |
| | 2.0 gpm max. | <u>408157150</u> | <u>408157010</u> |
| | 2.2 gpm max. | <u>408153150</u> | <u>408153010</u> |
| | 8.0 l/min | <u>408154150</u> | <u>408154010</u> |