



# OF-TYPE CHECK VALVES

**Features:** improved flow

- Nominal size: 7 – 20 mm
- Installation: in or against direction of flow
- Design: open version, without retaining tabs

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF7/DN6	0.9 - 7.8	0.2 - 2.1	<a href="#">314285000</a>	7.05 mm
OF10/DN8	3.0 - 16.2	0.8 - 4.3	<a href="#">314208000</a>	10.1 mm
OF15/DN15	12.6 - 45.0	3.3 - 11.9	<a href="#">310006000</a>	15.1 mm
OF20/DN20	24.0 - 81.0	6.3 - 21.4	<a href="#">314520000</a>	20.1 mm

## For high tech and hot water applications (-HT):

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF10/DN6-HT	2.0 - 16.2	0.5 - 4.3	<a href="#">314394000</a>	10.1 mm
OF15/DN15-HT	12.6 - 45.0	3.3 - 11.9	<a href="#">310024000</a>	15.1 mm

## With integrated pressure relief (-PR):

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF15/DN15-PR	12.6 - 45.0	3.3 - 11.9	<a href="#">310069000</a>	15.1 mm
OF20/DN20-PR	24.0 - 81.0	6.3 - 21.4	<a href="#">314289000</a>	20.1 mm