



flow, stop and go®



OF-TYPE CHECK VALVES

Features: improved flow

- Nominal size: 7 – 20 mm
- Installation: in or against direction of flow
- Design: open version, without retaining tabs

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF7/DN6	0.9 - 7.8	0.2 - 2.1	314285000	7.05 mm
OF10/DN8	3.0 - 16.2	0.8 - 4.3	314208000	10.1 mm
OF15/DN15	12.6 - 45.0	3.3 - 11.9	310006000	15.1 mm
OF20/DN20	24.0 - 81.0	6.3 - 21.4	314520000	20.1 mm

For high tech and hot water applications (-HT):

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF10/DN6-HT	1,8 - 16.2	0.5 - 4.3	314394000	10.1 mm
OF15/DN15-HT	12.6 - 45.0	3.3 - 11.9	310024000	15.1 mm

With integrated pressure relief (-PR):

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF15/DN15-PR	12.6 - 45.0	3.3 - 11.9	310069000	15.1 mm
OF20/DN20-PR	24.0 - 81.0	6.3 - 21.4	314289000	20.1 mm