




flow, stop and go®



SHORTY AERATORS


STD size, aerated stream with enhanced stream technology

PCA® Dual-Core (DC) models

Color code	Flow rate	STD insert	Female M22x1	Male M24x1
	1.0 gpm max.	<u>4029130005</u>	<u>4029132335</u>	<u>4029132435</u>
	1.2 gpm max.	<u>4029140005</u>	<u>4029142335</u>	<u>4029142435</u>
	1.5 gpm max.	<u>4029150005</u>	<u>4029152335</u>	<u>4029152435</u>
	1.75 gpm max.	<u>4029170005</u>	<u>4029172335</u>	<u>4029172435</u>
	2.1 gpm max.	<u>4029160005</u>	<u>4029162335</u>	<u>4029162435</u>

V+ model

Color code		Flow rate	STD insert	Female M22x1	Male M24x1
	V	V+ optimal performance and aeration from 0.5 to 1.5 bar	<u>4039310005</u>	<u>4039312335</u>	<u>4039312435</u>



SHORTY HONEYCOMB® AERATORS


STD size, aerated stream

Models with restrictor

Color code	Flow rate	STD insert short	Female M22×1 short	Male M24×1 short	Crown housing M24×1
	v optimal performance and aeration from 0.2 to 1.0 bar	403930000	403930233	403930243	403930M33

PCA® models

Color code	Flow rate	STD insert short	Female M22×1 shorty	Male M24×1 short	Crown housing M24×1
	1.0 gpm max.	402958000	402958233	402958243	402958M33
	1.2 gpm max.	402960000	402960233	402960243	402960M33
	5.0 l/min	402951000	402951233	402951243	402951M33
	1.5 gpm max.	402956000	402956233	402956243	402956M33
	1.75 gpm max.	402961000	402961233	402961243	402961M33
	7.0 l/min	402955000	402955233	402955243	402955M33
	2.0 gpm max.	402957000	402957233	402957243	402957M33
	2.2 gpm max.	402953000	402953233	402953243	402953M33
	8.0 l/min	402954000	402954233	402954243	402954M33



SHORTY HONEYCOMB® AERATORS


TT size, aerated stream

Models with restrictor

Color code	Flow rate	TT insert short	Male M18×1 short	Crown housing M18×1
	v optimal performance and aeration from 0.2 to 1.0 bar	<u>443930000</u>	<u>443930243</u>	<u>443930M33</u>

PCA® models

Color code	Flow rate	TT insert short	Male M18×1 short	Crown housing M18×1
	1.0 gpm max.	<u>443958000</u>	<u>443958243</u>	<u>443958M33</u>
	1.2 gpm max.	<u>443960000</u>	<u>443960243</u>	<u>443960M33</u>
	1.5 gpm max.	<u>443956000</u>	<u>443956243</u>	<u>443956M33</u>
	1.75 gpm max.	<u>443961000</u>	<u>443961243</u>	<u>443961M33</u>
	2.2 gpm max.	<u>443953000</u>	<u>443953243</u>	<u>443953M33</u>



SHORTY CASCADE® SLC® AERATORS

STD size, aerated stream

Models with restrictor

Color code	Flow rate	STD insert short	Female M22×1 short	Male M24×1 short	Crown housing M24×1
	v optimal performance and aeration from 0.2 to 1.0 bar	400A30000	400A30243	400A30233	400A30M33

PCA® models

Color code	Flow rate	STD insert short	Female M22×1 shorty	Female M24×1 shorty	Crown housing M24×1
	1.0 gpm max.	400A58000	400A58233	400A58243	400A58M33
	1.2 gpm max.	400A60000	400A60233	400A60243	400A60M33
	5.0 l/min	400A51000	400A51233	400A51243	400A51M33
	1.5 gpm max.	400A56000	400A56233	400A56243	400A56M33
	1.75 gpm max.	400A61000	400A61233	400A61243	400A61M33
	7.0 l/min	400A55000	400A55233	400A55243	400A55M33
	2.0 gpm max.	400A57000	400A57233	400A57243	400A57M33
	2.2 gpm max.	400A53000	400A53233	400A53243	400A53M33
	8.0 l/min	400A54000	400A54233	400A54243	400A54M33



flow, stop and go®



SHORTY CASCADE® SLC® AERATORS

STD size, aerated stream

PCA® Dual-Core (DC) models

Color code	Flow rate	STD insert short
	1.0 gpm max.	400A13000
	1.2 gpm max.	400A14000
	1.5 gpm max.	400A15000
	1.75 gpm max.	400A17000
	2.0 gpm max.	400A16000