


A-TYPE FLOW REGULATORS



A

Bore diameter: 19.3 mm

Max. temperature: 65°C / 150°F

Pressure range: 1-10 bar / 15-145 psi

color flow regulator	designation	flow rate	part number	divergent pressure range
	A	5.0 l/min	586010100	1.2-10 bar / 0.08-145 psi
	A	6.0 l/min	586012100	1.2-10 bar / 0.08-145 psi
	A	6.5 l/min	586013100	1.2-10 bar / 0.08-145 psi
	A	7.0 l/min	586014100	
	A	7.5 l/min	586015100	1.2-10 bar / 0.08-145 psi
	A	8.0 l/min	586016100	
	A	8.5 l/min	586017100	1.2-10 bar / 0.08-145 psi
	A	9.0 l/min	586018100	
	A	10.0 l/min	586020100	
	A	12.0 l/min	586024100	
	A	13.0 l/min	586026100	
	A	14.0 l/min	586028100	
	A	16.0 l/min	586032100	
	A	18.0 l/min	586036100	
	A	20.0 l/min	586040100	
	A	22.0 l/min	586044100	
	A	26.5 l/min	586046100	



flow, stop and go®



A-HT

Feature: High temperature

Bore diameter: 19.3 mm

Max. temperature: 80°C / 176°F

Pressure range: 1-8 bar / 15-116 psi

color flow regulator	designation	flow rate	part number
	A-HT	6.0 l/min	<u>587326100</u>
	A-HT	7.5 l/min	<u>587327100</u>
	A-HT	8.0 l/min	<u>587328100</u>
	A-HT	9.4 l/min	<u>587329100</u>
	A-HT	12.0 l/min	<u>587330100</u>