

# TROJAN LITHIUM-ION CHARGER COMPATIBILITY GUIDE

Charger firmware should be kept up to date for optimum performance. Trojan Battery makes no warranty as to compatibility with any specific equipment. Review product specifications for additional information.

**NOTE:** Starting charge rates assume a battery temperature of 68°F (20°C) to 113°F (45°C). Refer to the battery specific User's Guide for charge rates outside of this temperature range.



## 36V TROJAN PREFERRED CHARGERS

SUPPLIER / MODEL	TROJAN PN / MODEL NUMBER	WATTAGE	BATTERY PROFILE	APPLICATION NOTES
Trojan Fan Charger	10002335	600	Trojan Lithium	-
Lester Summit II	10001397	650	22740 V3	System profile 21046



## 48V TROJAN PREFERRED CHARGERS

SUPPLIER / MODEL	TROJAN PN / MODEL NUMBER	WATTAGE	BATTERY PROFILE	APPLICATION NOTES
Trojan Fan Charger	10001966	720	Trojan Lithium	-
Trojan Fan Charger	10002336	840	Trojan Lithium	-
Trojan Fan Charger	10002327	1200	Trojan Lithium	-
Lester TT650	10002339	650	22762	-
Lester Summit II	10001398 / 29700	650	22762	System profile 21046
Lester Summit II	10001965 / 28750	1050	22985	System profile 21046

## 48V COMPATIBLE AFTERMARKET CHARGERS\*

MANUFACTURER	MODELS	BATTERY PROFILE
Delta Q	IC Series, RC Series, QUIC Series	261
Eagle HF Series	I48180B; i4818CH; ES0800-48V001	Trojan Lithium
SPE	CBHF2	Trojan Lithium

\* Charging algorithms may not be compatible with all charger variants. Consult the charger manufacturer for information on setting the correct charging profile.


\* Compatible chargers should not be used if the battery profile is not properly set up or configured.

# TROJAN LITHIUM-ION CHARGER COMPATIBILITY GUIDE



## 72V TROJAN PREFERRED CHARGERS

SUPPLIER / MODEL	TROJAN PN / MODEL NUMBER	WATTAGE	BATTERY PROFILE	APPLICATION NOTES
Trojan Fan Charger	10002337	840	Trojan Lithium	-



Charger Compatibility for discontinued Lithium GC2 products can be found here.