

TROJAN LITHIUM-ION CHARGER COMPATIBILITY GUIDE



Battery Voltage	Charger Model Number	Wattage	Battery Profile	Application Notes
48	Lester Summit II Model 30410 V2 Rev 06	1050	22985	System Profile 21046
48	Lester Summit II Model 30600	650	22762	System Profile 21046
48	Standard Trojan Fan Charger	720	Trojan Lithium	
48	Eagle Performance Series I4818LITH & I4818CH	900	Trojan GC2 LiON	48V/18A
48	Delta Q QUIQ Model 912-4800	1000	261	
48	Delta Q Model RC-900-U48D	900	261	Part number 944-003
48	Delta Q Model IC-900-048-COMM	900	261	Part number 942-010
48	SPE CBHF2 48-15	720	Trojan Lithium	
48	SPE CBHF2 48-20	960	Trojan Lithium	

Requirements Utilized for Charger Qualifications

Starting rates need to be within specified start of charge rate for 48 volt products*

- TR-48-170-HP..... < 171A
- TR-48-170-M..... < 171A
- TR-48-110-M..... < 105A

Charger firmware should be kept up to date for optimum performance. Contact charger manufacturer for firmware updates. Informational purposes only. Equipment may vary. Trojan Battery Co. makes no warranty as to compatibility with any specific equipment. Review product specifications for additional information.

*Starting charge rates assume a battery temperature of 68°F (20°C) to 113°F (45°C). Refer to the battery specific User's Guide for charge rates outside of this temperature range.



Charger Compatibility for discontinued Lithium GC2 products can be found here.

