



RVX2-POLE INSTALLATION SHEET

Redvision's external double pole mounting bracket provides elegant mounting for the X-Series™ range of rugged PTZ's and the VEGA™ Rugged housings. To facilitate mounting a camera to a pole, the associated wall bracket is required in conjunction with the RVX2 POLE bracket. This bracket will clamp poles between 60 and 90mm diameter.

To mount the Pole bracket, remove the 4 off M8 screws to separate the 2 halves of the bracket assembly. Support the free half of the bracket containing the threaded M8 inserts with the oval cable entry slot towards the top of the pole. Fix the other half of the bracket clamping the pole, with the oval cable entry slot at the top using the 4 off M8 screws and locking washers provided.

Once the Pole bracket has been fully secured, use the relevant socket cap fixings (as detailed below) provided to secure the wall bracket(s).

Contents

- 1 x RVX2 Pole Clamp

Fixings to clamp the pole:

- 4 x M8 x 130 Hex Head Pozi Screws
- 4 x M8 Nuts
- 8 x M8 Plain Washers
- 4 x M8 Spring Washers

Fixings for new generation brackets:

- 4 x M8 x 25 Socket Cap Screws
- 8 x M8 Plain washer
- 4 x M8 Nyloc Nut
- 1 x M6 Allen key

Fixings for older model brackets:

- 4 x M6 x 16 Socket Cap Screws
- 4 x M6 Spring Washers
- 4 x M6 Plain Washers
- 1 x 5mm Allen Key

Fixings for VEGA brackets:

- 3 x M6 x 20 Socket Cap Screws
- 6 x M6 Plain washer
- 3 x M6 Plain Nut
- 3 x M6 Spring Washer
- 1 x M5 Allen key