



## PREMIUM SHAKER VIBA X.30

»The 3<sup>rd</sup> generation!  
Our best  
PoS expert«

Made to last!  
Most silent shaker available

- | Varnishes
- | Dispersions
- | many other liquids

### smartCONNECT

Optional: Full connectivity with the cloud or local computer at PoS. Connect VIBA wirelessly for tracking and analysing service and performance data. smartCONNECT can be retrofitted to all Collomix shakers and mixers.

### Install & Forget

Designed to last and be reliable – no matter what happens at PoS – Automatic door and clamping mechanics are protected against paint spills. Service calls reduced to a minimum thanks to best “Collomix” durability.

### Fast & smartMIX

Short and effective mixing times. Highest throughput at PoS. Best ergonomics thanks to self-opening integral door and smartMIX (single button operation, intuitive mixing intelligence and intelligent clamping control ICC).



## VIBA | X.30

Low throughput

Medium throughput

High throughput

Very high throughput

PREMIUM  
SHAKER

**VIBA**  
X.30

## Features

- Intelligent Clamping Control (ICC) reduces paint spills to a minimum – unique in the market
- New integral door design for highest reliability and optimal space-saving at PoS
- Auto-Open-Door-Function and roller at loading board for fast and easy loading
- Spindle cover for optimal protection and handle fixation
- Low noise emission at PoS, since particularly smooth-running and low-vibration
- Convenient installation using transport rollers and adjustment-free 3-foot installation
- Reduction in service costs as all components are easily accessible
- Made to last – install and forget!

| **VIBA X.30 V:** Unrivalled flexibility when using a wide range of containers and materials due to individually configurable mixing frequencies

## OPTIONAL

smart**CONNECT**

## Technical data

CONTAINER	VIBA X.30	VIBA X.30 V
Max. mixing weight	40 kg	40 kg
Rec. continuous working weight	30 kg	30 kg
Container height	50 - 400 mm	50 - 400 mm
Mixing plate dimensions	370 x 360 mm	370 x 360 mm
Top clamping plate dimensions	350 x 360 mm	350 x 360 mm
Container type	round / oval / metal / plastic	round / oval / metal / plastic
Multiple containers at the same time	yes	yes
PERFORMANCE		
Power supply	230 V / 50 Hz	230-240 V / 50-60 Hz
Motor output	0.9 kW	0.9 kW / frequency converter
Variable speed	no	Up to 6 speed intervals per mixing program
Recommended mixed throughput	medium to high	medium to high
OPERATION		
Mixing times	3 programmable times	3 mixing programmes
Clamping pressure	automatic - depending on 3 selectable containers heights	automatic - depending on 3 selectable containers heights
Door option	automatic integral door	automatic integral door
Loading type	Push & Slide incl. loading board	Push & Slide incl. loading board
Loading board height	497 mm (+ 30 mm)	497 mm (+ 30 mm)
Can be combined with roller conveyor	yes	yes
SHIPPING AND INSTALLATION		
Machine dimensions (W x D x H)	735 x 587 x 1207 mm	735 x 587 x 1207 mm
Machine weight	147 kg	147 kg
Transport rollers	yes	yes
Installation	adjustment-free 3-foot installation	adjustment-free 3-foot installation
SERVICE		
Splash guard index	Spindle cover	Spindle cover



**Collomix GmbH**

Daimlerstraße 9

85080 Gaimersheim

Germany

**P:** +49 ( 0 ) 8458 / 32 98 0

**F:** +49 ( 0 ) 8458 / 32 98 30

**E:** info@collomix.de

colortec.collomix.com