



# »The Push & SlideExpert«

## Outstanding ergonomics in production use

Facade paints

Plasters

Dispersions

Industrial coatings

#### Production operations!

Designed for production operations in industry and paint wholesale, in conjunction with roller conveyor systems.

#### Powerful

Outstanding output and short mixing times for up to 50 kg of mix thanks to the powerful drive concept.

#### Ergonomic

Ergonomic and time-saving mixer loading thanks to a Push & Slide system that doesn't put strain on the back.





Low throughput

Medium throughput

High throughpu

Very high throughput



#### Features

- High level of reliability due to robust mixing unit. Proven in practice 10,000 times over
- Smooth-running, even with large and heavy containers
- Particularly kind to containers due to biaxial mixing process, even for highly viscous materials
- Powerful drive unit and drive elements for reliable and effective operation
- Space-saving, fully automatic sliding door
- Reliable operation and low servicing requirements due to high-quality components
- Can be combined as a system with high volume dispensers or TINTA dispensers
- Automatic handle fixation system for fast loading and unloading

#### | Technical data

Splash guard index

Power supply  230 V / 50 Hz (110 V / 60 Hz optional)  Motor output  1.5 kW  Max. speed  140 rpm (programmable)  Rec. mixed throughput  high – very high  OPERATION  Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	CONTAINER	
Container height 130 – 445 mm  Max. container diameter 365 mm  Container type round / oval / metal / plastic  Multiple containers at the same time yes  PERFORMANCE  Power supply 230 V / 50 Hz (110 V / 60 Hz optional)  Motor output 1.5 kW  Max. speed 140 rpm (programmable)  Rec. mixed throughput high – very high  OPERATION  Mixing times 3 programmable times  Clamping pressure automatic - depending on 3 selectable containers hights  Door option automatic sliding door  Loading type Push & slide (only with roller conveyer)  Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Max. mixing weight	50 kg
Max. container diameter  Container type  round / oval / metal / plastic  Wultiple containers at the same time  PERFORMANCE  Power supply  230 V / 50 Hz (110 V / 60 Hz optional)  Motor output  1.5 kW  Max. speed  140 rpm (programmable)  Rec. mixed throughput  DEFRATION  Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation	Rec. continuous working weight	35 kg
Container type round / oval / metal / plastic  Multiple containers at the same time yes  PERFORMANCE  Power supply 230 V / 50 Hz (110 V / 60 Hz optional)  Motor output 1.5 kW  Max. speed 140 rpm (programmable)  Rec. mixed throughput high - very high  OPERATION  Mixing times 3 programmable times  Clamping pressure automatic - depending on 3 selectable containers hights  Door option automatic sliding door  Loading type Push & slide (only with roller conveyer)  Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Container height	130 – 445 mm
Multiple containers at the same time  PERFORMANCE  Power supply  230 V / 50 Hz (110 V / 60 Hz optional)  Motor output  1.5 kW  Max. speed  140 rpm (programmable)  Rec. mixed throughput  high – very high  OPERATION  Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  Shipping dimensions (W x D x H)  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	Max. container diameter	365 mm
PERFORMANCE  Power supply  230 V / 50 Hz (110 V / 60 Hz optional)  Motor output  1.5 kW  Max. speed  140 rpm (programmable)  Rec. mixed throughput  high – very high  OPERATION  Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  Shipping dimensions (W x D x H)  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	Container type	round / oval / metal / plastic
Power supply  230 V / 50 Hz (110 V / 60 Hz optional)  Motor output  1.5 kW  Max. speed  140 rpm (programmable)  Rec. mixed throughput  high – very high  OPERATION  Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	Multiple containers at the same time	yes
Motor output  1.5 kW  Max. speed  140 rpm (programmable)  Rec. mixed throughput  high – very high  OPERATION  Mixing times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  automatic sliding door  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	PERFORMANCE	
Max. speed 140 rpm (programmable)  Rec. mixed throughput high – very high  OPERATION  Mixing times 3 programmable times  Clamping pressure automatic - depending on 3 selectable containers hights  Door option automatic sliding door  Loading type Push & slide (only with roller conveyer)  Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Power supply	230 V / 50 Hz (110 V / 60 Hz optional)
Rec. mixed throughput high – very high  OPERATION  Mixing times 3 programmable times  Clamping pressure automatic - depending on 3 selectable containers hights  Door option automatic sliding door  Loading type Push & slide (only with roller conveyer)  Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Motor output	1.5 kW
Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	Max. speed	140 rpm (programmable)
Mixing times  3 programmable times  Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  7 ransport rollers  yes  Installation  adjustable 4-foot installation	Rec. mixed throughput	high – very high
Clamping pressure  automatic - depending on 3 selectable containers hights  Door option  automatic sliding door  Loading type  Push & slide (only with roller conveyer)  Clamping plate / loading height  435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor  yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  850 x 865 x 1168 mm  Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  7 ransport rollers  yes  Installation  adjustable 4-foot installation	OPERATION	
Door option automatic sliding door  Loading type Push & slide (only with roller conveyer)  Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Mixing times	3 programmable times
Loading type Push & slide (only with roller conveyer)  Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Clamping pressure	automatic - depending on 3 selectable containers hights
Clamping plate / loading height 435 mm (+20 mm); with base frame up to 850 mm  Can be combined with roller conveyor yes  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H) 850 x 865 x 1168 mm  Machine weight 227 kg  Shipping dimensions (W x D x H) 1000 x 1000 x 1310 mm  Shipping weight 267 kg  Transport rollers yes  Installation adjustable 4-foot installation	Door option	automatic sliding door
Can be combined with roller conveyor  SHIPPING AND INSTALLATION  Machine dimensions (W x D x H)  Machine weight  Shipping dimensions (W x D x H)  Shipping weight  Car kg  Transport rollers  Installation  yes  yes  yes  yes	Loading type	Push & slide (only with roller conveyer)
Machine dimensions (W x D x H)  Machine weight  Shipping dimensions (W x D x H)  Shipping weight  227 kg  Shipping weight  267 kg  Transport rollers  yes  Installation  SHIPPING AND INSTALLATION  850 x 865 x 1168 mm  227 kg  1000 x 1000 x 1310 mm  267 kg  Transport rollers  yes	Clamping plate / loading height	435 mm (+20 mm); with base frame up to 850 mm
Machine dimensions (W x D x H)  850 x 865 x 1168 mm  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	Can be combined with roller conveyor	yes
Machine weight  227 kg  Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  Shipping weight  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	SHIPPING AND INSTALLATION	
Shipping dimensions (W x D x H)  1000 x 1000 x 1310 mm  267 kg  Transport rollers  yes  Installation  adjustable 4-foot installation	Machine dimensions (W x D x H)	850 x 865 x 1168 mm
Shipping weight 267 kg  Transport rollers yes Installation adjustable 4-foot installation	Machine weight	227 kg
Transport rollers yes Installation adjustable 4-foot installation	Shipping dimensions (W x D x H)	1000 x 1000 x 1310 mm
Installation adjustable 4-foot installation	Shipping weight	267 kg
	Transport rollers	yes
Service	Installation	adjustable 4-foot installation
	SERVICE	

no splash guard

### **Collomix**

#### **Collomix GmbH**

Daimlerstraße 9 85080 Gaimersheim Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.de