



## GYROSCOPIC MIXER **ROTA | 400**

### »The Modern Mixer«

Outstanding ergonomics meets  
splashproof design

- | Dispersions
- | Facade paints
- | Plasters
- | Wood protection

#### Reliable

Virtually no downtimes caused by dirty drive and clamping elements due to unique (patented) protection mechanism.

#### Ergonomic

Outstanding ergonomics as minimal effort is required for loading and unloading. Machine loading that doesn't put strain on the back due to Push & Slide.

#### Quick

Automatic handle fixation and integral door with Auto Open function. The mixer is waiting for you - not you for the mixer.



GYROSCOPIC  
MIXER

**ROTA**  
400

## Features

- Simple and space-saving handling due to automatically opening integral door
- High level of mixing efficiency with very short mixing times
- Smooth-running with large and heavy containers
- Low noise emission at the POS due to maintenance-free toothed belt drive
- Particularly kind to containers due to biaxial mixing of even viscous materials
- Reduction in service costs as all the components are easy to access
- System integration in shop solutions; can be combined with roller conveyors
- Can be ideally expanded with Collomix TINTA dispensers

## Technical data

CONTAINER	
Max. mixing weight	40 kg
Rec. continuous working weight	30 kg
Container height	60 - 400 mm
Max. container diameter	round: 350 mm / oval: 360 x 330 mm
Container type	round / oval / metal / plastic
Multiple containers at the same time	yes
PERFORMANCE	
Power supply	230 V / 50 Hz (110 V / 60 Hz optional)
Motor output	1.1 kW
Max. speed	145 rpm (programmable)
Rec. mixed throughput	medium
OPERATION	
Mixing times	3 programmable times
Clamping pressure	automatic - depending on 3 selectable containers heights
Door option	automatic integral door
Loading type	Push & Slide incl. loading board
Clamping plate / loading height	455 mm (+ 15 mm)
Can be combined with roller conveyor	yes
SHIPPING AND INSTALLATION	
Machine dimensions (W x D x H)	780 x 987 x 1186 mm
Machine weight	190 kg
Shipping dimensions (W x D x H)	800 x 1200 x 1330 mm
Shipping weight	215 kg
Transport rollers	yes
Installation	adjustable 4-foot installation
SERVICE	
Splash guard index	Special splash guard - complete protection



**Collomix GmbH**

Daimlerstraße 9

85080 Gaimersheim

Germany

**P:** +49 ( 0 ) 8458 / 32 98 0

**F:** +49 ( 0 ) 8458 / 32 98 30

**E:** [info@collomix.de](mailto:info@collomix.de)

[www.collomix.de](http://www.collomix.de)