



SHAKER

VIBA | 300/330

»The POS-Expert«

Fast and ergonomic
in paint stores

| Varnishes

| Dispersions

Safe

Service calls reduced to a minimum by protecting clamping mechanism against pollution and Intelligent Clamping Control (ICC)

Fast

Short mixing times and high throughput thanks to proven high-performance drive and speed. Ideal for requirements at the point of sale.

Ergonomical

Unrivalled user-friendliness due to maximum working ergonomics thanks to the self opening integral door.



VIBA | 300/330

Low throughput

Medium throughput

High throughput

Very high throughput

SHAKER

VIBA
300 / 330

Features

- Easy to handle and space-saving due to integral door, with Auto Open function
- Low noise emission at the POS, since particularly smooth-running and low-vibration
- Reliable processing of mixing jobs thanks to long service life
- Reduction in service costs as all the components are easy to access
- Convenient installation using transport rollers and adjustment-free 3-point installation
- System integration in shop solutions; can be combined with roller conveyors
- Can be ideally combined with Collomix TINTA dispensers

| **VIBA 330:** Unrivalled flexibility when using a wide range of containers and materials due to individually configurable mixing frequencies

Technical data

CONTAINER	VIBA 300	VIBA 330
Max. mixing weight	40 kg	40 kg
Rec. continuous working weight	30 kg	30 kg
Container height	50 - 400 mm	50 - 400 mm
Mixing plate dimensions	370 x 360 mm	370 x 360 mm
Top clamping plate dimensions	350 x 360 mm	350 x 360 mm
Container type	round / oval / metal / plastic	round / oval / metal / plastic
Multiple containers at the same time	yes	yes
PERFORMANCE		
Power supply	230 V / 50 Hz (110 V / 60 Hz optional)	230 V / 50 Hz (110 V / 60 Hz optional)
Motor output	0.9 kW	0.9 kW / frequency converter
Default speed	690 rpm	690 rpm
Variable speed	no	Up to 6 speed intervals per mixing program
Recommended mixed throughput	medium to high	medium to high
OPERATION		
Mixing times	3 programmable times	3 mixing programmes
Clamping pressure	automatic - depending on 2 selectable containers heights	automatic - depending on 2 selectable containers heights
Door option	automatic integral door	automatic integral door
Loading type	Push & Slide incl. loading board	Push & Slide incl. loading board
Loading board height	495 mm (+ 30 mm)	495 mm (+ 30 mm)
Can be combined with roller conveyor	yes	yes
SHIPPING AND INSTALLATION		
Machine dimensions (W x D x H)	725 x 583 x 1231 mm	725 x 583 x 1231 mm
Machine weight	150 kg	150 kg
Shipping dimensions (W x D x H)	800 x 620 x 1380 mm	800 x 620 x 1380 mm
Shipping weight	170 kg	170 kg
Transport rollers	yes	yes
Installation	adjustment-free 3-foot installation	adjustment-free 3-foot installation
SERVICE		
Splash guard index	Spindle cover	Spindle cover



Collomix GmbH

Daimlerstraße 9

85080 Gaimersheim

Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.de