





Materials and applications





XM-3 900 forced-action mixer

- Forced-action mixer with high torque for fast and optimised mixing with perfect material characteristics.
- Ideal for industrial floor coatings, sythetic resin systems, concrete renovation, ETICS, blast furnace construction, sewer and water pipe renovation, floor construction, sports area coverings, etc.
- 2 mixing bodies with edge scraper, plus 2 different mixing speeds
- High hourly throughput possible thanks to alternating mixing buckets (-1 to /h)
- Timer (90, 180 sec., permanent mode)
- A transport trolley accessory completes the system
- Recommended by leading building chemical manufacturers



Material (weight without the addition of water) *WS1 **WS2

Earth-moist concrete -16 mm grain size	•	•
Cement screed	0	•
Prebagged loam rendering without fibres	0	
Heat insulation plaster	•	
Breathable lightweight render	0	•
Natural stone mortar/cobblestone mortar	0	
2K pavement grout (up to 1.2 mm)	•	
Tile adhesive(flexible mortar)	•	•
thin/fluid screed types	•	•
thin/fluid mortar types	O	•
Bonding agents as rendering base	-	•
Grout	O	•
Joint-sealing compounds	-	•
Bonding agents	•	•
2K seaming slurries	-	•
Levelling compounds	-	•
2K epoxy resin sand mixture	0	•
Heat insulation adhesive	0	
High-performance mortar (Flowstone)	0	
Restoration plaster	0	
2K re-profiling mortar	0	•
Cast concrete	0	•
Synthetic resin mortar	0	•
Synthetic resin coatings		•

Technical data

Mixing quantity:	up to 70 litres
Bucket capacity:	90 litres
Mixing tool output:	1.5 kW / 400 V
Speed of mixing tool:	2 x 185 1 x 670 rpm
Scraper speed:	40 rpm ⁻¹
Weight (empty):	117 kg
Dimensions:	107.5 x 75.8 x 84.5 cm
XM 3 - 400 V item no.:	39015
XM 160 mixing tool item no.:	70153
XM 195 mixing tool item no.:	70155
SR 160 mixing tool item no.:	70157
90 L mixing bucket item no.:	60261
Transport trolley item no.:	70183
90 L upgrade set item no.:	60318
•••••	•••••••••••••••••••••••••••••••••••••••

Your Collomix specialised dealers:



Product video







