

TORO



GYROSCOPIC
MIXER

TORO
neo



Features

- Auto-Sense Function – just press one button to start mixing process, can size is selected automatically
- Splash Guard avoids internal pollution of critical parts and helps to prevent expensive repairs
- Automatic handle-holder prevents rattling during the mixing process
- Low noise emission and smooth operation at Point-of-Sale
- Fast Loading / unloading of paint-can and takes a minimum effort due to Swing & Slide concept
- Fixed bottom-plate
- Easy handling and loading – even of heavy paint-cans – due to loading ramp
- Easy access to the interior results in low maintenance cost
- Fast and easy installation by one person due to extractable rollers
- Forms a perfect combination with Collomix TINTA dispenser

Technical data

CONTAINER	
Max. mixing weight	40 kg
Rec. continuous working weight	30 kg
Container height	60 - 400 mm
Max. container diameter	360 mm
Container type	round, oval, metal, plastic
PERFORMANCE	
Power supply	230 V / 50 Hz (opt. 110 V / 60 Hz)
Motor output	1.1 KW
Max. speed	145 rpm (programmable, variable)
Rec. mixing throughput	low to medium
Multiple can mixing	yes
OPERATION	
Mixing times	3 programmable times
Clamping pressure & mixing speed	automatic - depending on 3 selectable containers hights
Door option	manual swing door (door opening left or right)
Loading type	Swing & Slide with loading ramp
Clamping plate / loading height	385 mm (± 10 mm)
SHIPPING AND INSTALLATION	
Machine dimensions (W x D x H)	782 x 811 x 1007 mm
Machine weight	152 kg
Shipping dimensions (W x D x H)	800 x 900 x 1270 mm
Shipping weight	168 kg
Transport rollers	yes
Installation	adjustable 4-foot installation
SERVICE	
Splash guard index	large splash protection



Collomix GmbH

Daimlerstraße 9

85080 Gaimersheim

Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

colortec.collomix.com