HONDA
The Power of Dreams

How we move you.
CREATE ► TRANSCEND, AUGMENT



SPECIFICATIONS

TRANSALP

ENGINE	
Type	Liquid-Cooled OHC 4-Stroke 8-Valve Parallel Twin with 270° Crank and Unicam
Displacement (cc)	755 cc
Bore & Stroke (mm)	87 x 63.5 mm
Compression Ratio	11.0:1
Max. Power Output	67.5kW @ 9,500 rpm
Max. Torque	75 Nm @ 7,250 rpm
FUEL SYSTEM	
Fuel Tank Capacity (L)	16.6 L
Fuel Consumption (WMTC)	24 Km/L
DRIVE TRAIN	
Clutch Type	Multiplate Wet Clutch
Transmission Type	6-Speed Manual Transmission
Final Drive	Chain
FRAME	
Type/Material	Diamond Type/Steel
DIMENSIONS and WEIGHT	
Dimensions L x W x H (mm)	2,325 X 838 X 1,455 mm
Wheelbase (mm)	1,560 mm
Caster Angle	27°
Trail (mm)	111 mm
Seat Height (mm)	855 mm
Ground Clearance (mm)	210 mm
Curb Weight (Kg)	210 Kg
Turning Radius (m)	2.6 m

SUSPENSION	
Front Type	Showa 43mm SFF-CA USD – 200mm Travel
Rear Type	Monoshock Damper, Pro-Link Swingarm, 190mm Travel
WHEELS	
Front Tire	90/90 - 21 M/C 54H
Rear Tire	150/70 - R 18 M/C 70H
BRAKES	
ABS Type	2-Channel
Front Type	Axial mounted two-piston brake caliper, 310mm floating double disc
Rear Type	Single piston caliper, 256 single disc
INSTRUMENTS and ELECTRONICS	
Instruments	TFT
Security System	HISS
Head light	LED
Tail Light	LED

COLOR CHART

- Ross White
- Graphite Black

Adventure is out there and waiting for you. Face it with **The XL750 Transalp**, the perfect companion to every new experience. Built for both urban landscapes and rough mountain trails, its sporty build is built to go the distance, providing you both power and comfort for long rides. Look unfazed as you ride in style with a tough yet aerodynamic bike for life's best escapades. Ride high with your own XL750 Transalp today.





5.0inch TFT full color LED meter



Dual LED projector headlights



Honda RoadSync Smartphone Connectivity

Customer Care Hotline:
PLDT : 1-800-10HONDAPH-4663274
Email : customerservice@hondaph.com

Honda Philippines, Inc

www.hondaph.com/honda-bigbikes/