

CLARE SAFETY DATA SHEET FOR CLARE INTERIOR PAINTS

The following Safety Data Sheet (SDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200 and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Clare, Inc.; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following SDS supersedes any previously issued SDS for each product covered. The reader is advised to destroy any obsolete SDS and refer only to this SDS. As permitted by OSHA, each SDS may apply to a class of products which have similar hazards and contents.

PRODUCTS COVERED BY THIS SDS: *Listed Below*

PRODUCT NAME	CLARE SKU
CLARE WALL PAINT: Perfect Eggshell	PNT100-LT, PNT100-MD, PNT100-DP
CLARE TRIM PAINT: Subtle Semi-Gloss	PNT200-LT, PNT200-MD, PNT200-DP
CLARE CEILING PAINT: Flat White	PNT300
CLARE PRIMER: Perfect Eggshell	PNT400

SECTION 1: *Identification*

PRODUCT IDENTIFIER See above for a list of products covered	PHONE NUMBER (646) 847-7746	RECOMMENDED USE Architectural Coating
MANUFACTURER NAME Clare, Inc.	EMERGENCY PHONE NUMBER (646) 627-7234	RESTRICTIONS ON USE No Information Available
ADDRESS 246 5th Avenue, New York, NY 10001	PRODUCT TYPE Waterborne Paint	

SECTION 2: *Hazard(s) Identification*

GHS CLASSIFICATION Not Applicable	PRECAUTIONARY STATEMENTS HEALTH & SAFETY: Do not ingest paint, and avoid inhaling spray mist. Make sure your space is well-ventilated while painting and keep paint out of reach of children. Immediately wash skin that has come into contact with paint, and close your paint container tightly when you're finished. CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. Exposure to lead or asbestos can be very hazardous to your health. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by waterwashing all surfaces. For more information, visit clare.com/Safety or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or/asbestos, or contact your state or local Health Department. DISPOSAL: Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: clare.com/safety .
LABEL ELEMENTS This consumer product is exempt from OSHA GHS-HCS labeling requirements.	
HAZARDS NOT OTHERWISE CLASSIFIED None	

SECTION 3: *Composition/Information on Ingredients*

HAZARDOUS INGREDIENTS

No reportable hazardous ingredients.

NOTE

Potential unusual allergic sensitivity to trace ingredients of this product can be minimized by following recommended procedures for safe handling, storage, disposal, and use.

SECTION 4: *First-Aid Measures*

MOST IMPORTANT SYMPTOMS AND EFFECTS

May cause mild irritation to eyes, skin, respiratory and gastrointestinal tracts. Slight dizziness, nausea, and headaches are possible.

NOTE TO FIRST AID PROVIDERS

Call for medical assistance if symptoms persist.

REQUIRED TREATMENT

EYES: If paint gets in your eyes, immediately flush them with water for 15 minutes.

SKIN: If paints comes into contact with your skin, immediately wash thoroughly with soap and water.

INHALATION: If paint is inhaled, move to fresh air.

INGESTION: If paint is swallowed, immediately drink 1 to 2 glasses of water.

SECTION 5: *Fire-Fighting Measures*

SUITABLE EXTINGUISHING TECHNIQUES

Foam, alcohol foam, CO₂, and chemical water fog.

SPECIAL EQUIPMENT AND PRECAUTIONS

Use self-contained breathing apparatus in confined spaces. Observe recommendation procedures for handling ordinary combustible materials.

CHEMICAL HAZARDS FROM FIRE

Liquid material is non-combustible, but dried films are capable of supporting combustion when in contact with open flames. Closed containers may rupture when subjected to extreme heat.

POSSIBILITY OF HAZARDOUS REACTIONS

Combustion can produce carbon monoxide and/or carbon dioxide.

SECTION 6: *Accidental Release Measures*

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Avoid contact with eyes, skin, and clothing. Make sure your space is well-ventilated while painting. Wear waterproof gloves to avoid skin contact. Keep children and pets away from spilled paint. Prevent paint from entering drains.

METHODS FOR CONTAINMENT AND CLEANUP

Soak up spilled paint with inert material. Scoop up excess paint and pour into suitable containers for disposal. Use paper or cloth wipes to clean up small spills. Allow to dry before disposal.

SECTION 7: *Handling & Storage*

SAFE HANDLING PRECAUTIONS

Keep containers closed when not in use. Do not stack containers more than three high. Secure loads against shifting in transportation. Use only an appropriate tool to open containers, such as the provided Clare paint can opener.

SAFE STORAGE CONDITIONS

Store in a cool, well-ventilated area. Maintain temperatures between 0°F and 90°F. Avoid exposure to direct sunlight, heat, or flame. Inspect containers periodically for leaks.

INCOMPATIBILITIES

Do not handle or store near water-reactive materials, strong oxidizers, acids, or alkalis.

SECTION 8: *Personal Protection*

OSHA'S PERMISSIBLE EXPOSURE LIMITS (PELS) AND ACGIH

THRESHOLD LIMIT VALUES (TLVS)

No reportable hazardous ingredients.

ENGINEERING CONTROLS

Use signs or barriers to restrict access to painting work area.

VENTILATION

Make sure your space is well-ventilated while painting.

HYGENIC PRACTICES

Wash hands and face before eating or drinking. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT

EYE PROTECTION: Use safety glasses with side shields, goggles, or face shield to protect eyes.

SKIN PROTECTION: Use waterproof gloves (latex, vinyl, rubber, or neoprene) to avoid skin contact.

RESPIRATORY PROTECTION: For spray application, use particulate filter mask to avoid breathing in spray mist. People with unusual allergic sensitivity may need an organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Waterproof head covering and general protective clothing are recommended for protection as necessary.

SECTION 9: *Physical & Chemical Properties*

APPEARANCE

Opaque Liquid Dispersion

VAPOR PRESSURE

Same As Water Vapor

ODOR

Very Mild Odor

VAPOR DENSITY

Same As Water Vapor

ODOR THRESHOLD

No Information Available

SPECIFIC GRAVITY

~1.4 (H₂O = 1)

PH AS SUPPLIED

~8.5

SOLUBILITY IN WATER

Partly Soluble

FREEZING POINT

0° C / 32° F

PARTITION COEFFICIENT

No Information Available

BOILING POINT

100° C / 212° F

AUTO-IGNITION TEMP

Not Applicable

FLASH POINT

Not Applicable

DECOMPOSITION TEMP

No Information Available

EVAPORATION RATE

Same As Water

VISCOSITY

85 – 115 Ku

FLAMMABILITY

Not Applicable

PERCENT SOLIDS

By Vol: ~35% By Wt: ~50%

UPPER EXPLOSIVE LIMIT

Not Applicable

PERCENT VOLATILE

By Vol: ~65% By Wt: ~50%

LOWER EXPLOSIVE LIMIT

Not Applicable

SECTION 10: *Stability & Reactivity*

REACTIVITY

Reactivity not known to occur under normal conditions.

CHEMICAL STABILITY

Stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS

Polymerization will not occur.

CONDITIONS TO AVOID

Avoid storage or use at temperatures below 40° F.

INCOMPATIBLE MATERIALS

Avoid water-reactive materials, strong oxidizers, acids, and alkalis.

POSSIBILITY OF HAZARDOUS REACTIONS

Combustion can produce carbon monoxide and/or carbon dioxide.

SECTION 11: *Toxicological Information*

LIKELY ROUTES OF EXPOSURE

Eye and skin contact, inhalation, ingestion.

SYMPTOMS OF OVEREXPOSURE

May cause mild irritation to eyes, skin, respiratory and gastrointestinal tracts. Slight dizziness, nausea, and headaches are possible.

DELAYED OR CHRONIC EFFECTS

No evidence of delayed or chronic health effects associated with exposure.

NUMERICAL MEASURES OF TOXICITY

No Information Available

CARCINOGENICITY

Not Applicable

SECTION 12: *Ecological Information*

No Information Available

SECTION 13: *Disposal Considerations*

WASTE DISPOSAL METHOD

Dispose in accordance with all applicable local, state, and federal regulations. Local requirements may vary. Consult your sanitation department or state-designated environmental protection agency for more disposal options.

RCRA HAZARD CLASS

Non-hazardous

SECTION 14: *Transport Information*

This material is not subject to DOT, IATA/ICAO, Or IMO/IMDG transportation regulations. Acceptable for air transport as non-hazardous goods.

SECTION 15: *Regulatory Information*

U.S. FEDERAL REGULATIONS

TSCA: All components are listed in TSCA inventory or exempt.

CERCLA: Not listed as a hazardous substance.

SARA TITLE III: Not listed as a hazardous substance.

311/312 HAZARD CATEGORIES:
Not Applicable

313 REPORTABLE

INGREDIENTS: Not Applicable

STATE REGULATIONS

None

SECTION 16: *Other Information*

DATE OF PREPERATION

June 28, 2018

PREPARED BY

Clare, Inc.

MANUFACTURER NAME

Clare, Inc.

ADDRESS

246 5th Avenue, New York, NY 10001

PHONE NUMBER

(646) 847-7746

DISCLAIMER

The information conveyed here, while obtained from sources we consider reliable, is furnished by Clare, Inc. without any warranty (whether express or implied) as to its accuracy, adequacy, or applicability to any particular needs or circumstances.