

# CACTUS TECHNOLOGIES 2.5" Solid State Drive (SSD) 910S Pro Series



The Cactus Technologies Solid State Drive (SSD) - 910S Pro Series is a high capacity solid-state flash memory product that complies with the Serial ATA 3.0 standard and is functionally compatible with a SATA hard disk drive. Cactus Technologies® -910S Pro Series SSD provide up to 640GB of formatted storage capacity and have the added features of AES256 Encryption as well as Quick Erase via a hardware jumper.

## CACTUS SATA III SSD FEATURES

- INDUSTRY STANDARD 2.5" FORM FACTOR
- SSD CAPACITIES
  - 64GB to 640GB
- AES256 ENCRYPTION
- QUICK ERASE (512GB in <15 seconds)
- SUPPORTS SATA I/II/III  
1.5/3.0/6.0 GBPS TRANSFER RATE
- 5V OPERATION
- SUPPORTS:
  - ATA SMART Feature Set
  - ATA Security Feature Set
  - SATA NCQ w/ max. 32 Queue depth
  - SATA partial and slumber modes
- UNIQUE ELECTRONIC DEVICE ID
- UP TO 60K IOPS
- TRACEABILITY BARCODE
- RELIABILITY
  - High Data Reliability
  - High Shock & Vibration Tolerances
  - Wide Operating Temp Range
- 4-MILLION HOUR MTBF
- 5-YEAR WARRANTY



### PERFORMANCE

Read Data Transfer Rate  
up to 430MB/sec  
Write Data Transfer Rate  
up to 440MB/sec



### RELIABILITY

- Industrial Wear Leveling
- Industrial Error Checking & Correction
- Less Than 1 Error in  $10^{14}$  Bits Read
- MTBF 4,000,000 Hours



### ENVIRONMENTAL & POWER

Operating Temperature Range  
Standard                    0°C to 70°C  
Extended                    -45°C to +90°C



### POWER CONSUMPTION

	5.0V
Read	470mA
Write	660mA
Standby	230mA



### SHOCK & VIBRATION

Shock	3,000G
Vibration	20G peak-to-peak

CACTUS TECHNOLOGIES  
 2.5" Solid State Drive (SSD)  
**910S Pro Series**



**INDUSTRIAL GRADE SOLID STATE DRIVE**

→ INTERFACE	ANSI ATA8-ACS2 Spec; Serial ATA 3.0 Spec	
→ INTERFACE TRANSFER RATE	6.0Gb/sec	
→ POWER REQUIREMENT	DC Input Voltage	5V ± 10%
	Standby	230mA
	Read	470mA
	Write	660mA
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	0°C to 70°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	20G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	MTBF	4,000,000 Hours
	Data Reliability	less than 1 Error in 10 <sup>14</sup> bits read
→ CARD CAPACITY	64GB to 640GB	

Cactus Technologies Limited  
 Suite C, 15/F, Capital Trade Center  
 62 Tsun Yip Street, Kwun Tong  
 Kowloon, Hong Kong  
 Tel: +852-2797-2277  
 Email: sales@cactus-tech.com

Cactus USA  
 3112 Windsor Road  
 Suite A356  
 Austin, Texas 78703  
 Tel: (512) 775-0746  
 Email: americas@cactus-tech.com



www.cactus-tech.com