

Mannington®

Product Technical Information Sheet

Hardwood

Product Summary:

Pattern	Finished Size (nominal)	Source	Species	Face Type	Veneer Thickness	Weight/ Carton (lbs)	Sq. ft/ Carton	Cartons/ Pallet	Sq. ft/ Pallet	Pallets/ Container
Antigua: 9/16" Thickness (Nominal)										
Pacaya Mesquite	3", 5", 7" x up to 84"	Guatemala	Shiringa	Sawn	3 mm	59.09	35	44	1,540.00	18
Latitude Collection: 1/2" Thickness (Nominal)										
Prospect Park	7.5" x up to 83"	Vietnam	White Oak	Sliced	2 mm	45.19	25.77	50	1,245.00	20
Park City	7.5" x up to 83"	Vietnam	White Oak	Sliced	2 mm	45.19	25.77	50	1,245.00	20
Park City HB	7.5" x 37.5"	Vietnam	White Oak	Sliced	2 mm	40.12	23.4	36	842.40	29-30
Forest Park	7.5" x up to 83"	Vietnam	Hickory	Sliced	1.2 mm	45.19	25.77	50	1,288.50	20
Maison Collection: 9/16" Thickness (Nominal)										
Bastille	7" x up to 84"	Guatemala	Walnut	Sawn	3 mm	41.82	24.5	55	1,347.50	19
Chateau	7" x up to 84"	Guatemala	White Oak	Sawn	3 mm	43.64	24.5	55	1,347.50	19
Normandy Oak	7" x up to 84"	Guatemala	White Oak	Sawn	3 mm	43.64	24.5	55	1,347.50	19
Provence	7" x up to 84"	Guatemala	Hickory	Sawn	3 mm	44.09	24.5	55	1,347.50	19
Triumph	7" x up to 84"	Guatemala	Oak, Maple, Hickory	Sawn	3 mm	43.64	24.5	55	1,347.50	19
Versailles	7" x up to 84"	Guatemala	Maple	Sawn	3 mm	43.36	24.5	55	1,347.50	19
Artisan Walnut	7" x up to 84"	Guatemala	Walnut	Sawn	3 mm	41.82	24.5	55	1,347.50	20
Artisan Walnut HB	7" x 35"	Guatemala	Walnut	Sawn	3 mm	37	20.42	55	1,123.10	20
Provence HB	7" x 35"	Guatemala	Hickory	Sawn	3 mm	38	20.42	55	1,123.10	20
Other: Thickness Varies										
Bengal Bay	5" x up to 48"	Vietnam	Bengali	Sliced	1.5 mm	34.83	26.25	44	1,155.00	29
Bengal Bay Random	2", 3", 5" x up to 48"	Vietnam	Bengali	Sliced	1.5 mm	34.83	26.25	44	1,155.00	29
Iberian Hazelwood	6.5" x up to 84"	Guatemala	Hazelwood	Rotary	2 mm	44.79	37.13	48	1,782.24	21
Kodiak	5" x up to 48"	Guatemala	White Teak	Rotary	1.5 mm	43.75	40.00	32	1,280.00	32
Momentum	7.5" x up to 75"	Vietnam	White Oak	Sliced	1.2 mm	54.45	38.86	45	1,748.70	19
Monogram	8.6" x up to 86.6"	Vietnam	White Oak	Sawn	3 mm	65.70	31.26	40	1,250.40	18
Mountain View XL	6.57" x up to 83"	Guatemala	Hickory	Rotary	1.5 mm	46.88	37.13	48	1,782.24	20
Riverwalk	6.5" x up to 74.8"	Cambodia	White Oak	Sliced	1.2 mm	36.38	27.00	66	1,782.00	20
Sanctuary	9.5" x up to 87"	Vietnam	White Oak	Sawn	4 mm	63.71	28.42	40	1,136.80	18

Mannington®

Product Technical Information Sheet - Page 2

Construction:	Engineered Premium Hardwood
Gloss Level:	Low Lustre or Matte - varies by SKU
Overall Thickness:	Varies by SKU (refer to chart on page 1)
Wearlayer:	Polyurethane finish with aluminum oxide and enhanced scratch resistance
Origin:	Guatemala, Vietnam or Cambodia - varies by SKU (refer to chart on page 1)
Edge Style:	Full Bevel, Micro Bevel or Hand Sanded Bevel - varies by SKU
Installation:	Full glue, staple/nail (glue assist) or float
Warranty:	Varies by SKU

Product Performance Characteristics:

ANSI/HPVA EF01 Specification	Meets
Finish Adhesion (ASTM-D3359)	5B
Flame spread tunnel test (ASTM E-84)	Meets Class C
Radiant Panel (ASTM E-648)	Flooring - Greater than or equal to 45 watts /cm2, passes NFPA class 1
Static Load Limit	650 PSI (4.5 MPa)
ADAAG/ADA (ASTM-D2394)	Meet or Exceed Guideline for Flat Walking Surface
Environmental Certifications	LEED EQ 4.1 – If Mannington UltraSpread glue is used – Meets SCAQMD Rule #1168 LEED EQ 4.3 – FloorScore® Certified LEED EQ 4.4 – No added formaldehyde SCA Title VI: Complies – No added formaldehyde glues utilized CARB Phase 2: Complies – No added formaldehyde glues utilized

Installation & Safety:

- **Installation Instructions:** For complete installation guidelines, visit Mannington.com/HardwoodInstallation
- **California Prop 65:** Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard. For more information, visit P65Warnings.ca.gov
- **RFCI Recommended Work Practices:** Visit RFCI.com