



Product Technical Information Sheet

Product Summary:

Product(s):	Iberian Hazelwood
Width:	Nominal 6 1/2" (165mm)
Length:	Random up to 83 1/2" (2100 mm); average 80% full length boards per carton
Thickness:	Nominal 3/8" (9.0mm)
Gloss level:	Low Lustre (15 +/-3 on a 60 degree meter)
Wearlayer:	8 layer polyurethane finish with aluminum oxide and enhanced scratch resistance.
Construction:	5 ply engineered Premium Hardwood
Face:	Hazelwood (Betula Pubescens)
Face Thickness:	1.8 mm prior to final sanding
Origin:	Made in the Guatemala from European raw materials
Profile:	Full Bevel
Installation:	Full glue, staple, or nail
Packaging:	37.13 square feet per carton / 34.56 lbs per carton / 48 cartons per pallet
Warranty:	25 Year Residential



Product Technical Information Sheet – Page 2

Product performance characteristics:

*Abrasion Resistance: Minimum 500 cycles
(ASTM-D4060-90)*

*Finish Adhesion: 5B – 0% removal
(ASTM-D3359-95)*

*Flame spread tunnel test: Meets Class C, flamespread 40
(ASTM E-84)*

*Radiant Panel: Flooring - Greater than or equal to 45 watts /cm², passes NFPA class 1
(ASTM E-648)*

Static Load Limit: 650 PSI(4.5 MPa)

*ADAAG/ADA Meet or Exceed Guideline for Flat Walking Surface(0.6)
(ASTM-D2394)*

Environmental Certifications

LEED EQ 4.1 – If Mannington UltraSpread glue is used – Meets SCAQMD Rule #1168

LEED EQ 4.3 – FloorScore Certified