



## Product Technical Information Sheet

### Product Summary:

Product(s):	Rock Creek Plank
Width:	Nominal 6 1/2" (165.1 mm)
Length:	Random up to 48" (1219 mm);
Thickness:	Nominal 3/8" (8.4mm)
Gloss level:	Low Lustre (18 +/-3 on a 60 degree meter)
Wearlayer:	8 layer polyurethane finish with aluminum oxide and enhanced scratch resistance.
Construction:	5 ply engineered Premium Hardwood
Face:	Northern Red Oak (Quercus Rubra)
Face Thickness:	1.4 mm prior to final sanding
Origin:	Made in the USA – Lacey Compliant
Profile:	Micro Bevel
Installation:	Full glue, staple, or nail
Packaging:	30.5 square feet per carton / 35 lbs per carton / 30 cartons per pallet
Warranty:	25 Year Residential / 5 Year Commercial finish warranty



## Product Technical Information Sheet – Page 2

### Product performance characteristics:

*Abrasion Resistance: Minimum 500 cycles  
(ASTM-D4060-90)*

*Finish Adhesion: 5B – 0% removal  
(ASTM-D3359-95)*

*Flame spread tunnel test: Meets Class C, flamespread 40  
(ASTM E-84)*

*Radiant Panel: Flooring - Greater than or equal to 45 watts /cm<sup>2</sup>, passes NFPA class 1  
(ASTM E-648)*

*Static Load Limit: 650 PSI(4.5 MPa)*

*ADAAG/ADA Meet or Exceed Guideline for Flat Walking Surface(0.6)  
(ASTM-D2394)*

### Environmental Certifications

LEED EQ 4.1 – If Mannington UltraSpread glue is used – Meets SCAQMD Rule #1168

LEED EQ 4.3 – FloorScore Certified