

MANNINGTON®

Product Technical Information Sheet

Product Summary:

Product(s):	Mountain View XL
Width:	Nominal 6 1/2" (165mm)
Length:	Random up to 83 1/2" (2100 mm); average 70% full length boards per carton
Thickness:	Nominal 3/8" (9.0mm)
Gloss level:	Matte Finish (10 +/-3 on a 60 degree meter)
Wearlayer:	8 layer polyurethane finish with aluminum oxide and enhanced scratch resistance.
Construction:	5 ply engineered Premium Hardwood - No-Added Formaldehyde Adhesive system
Face:	Northern Hickory (Carya spp)
Face Thickness:	1.8 mm prior to final sanding
Origin:	Made in the Guatemala from US and European raw materials
Profile:	Full Bevel
Installation:	Full glue, staple, or nail
Packaging:	37.13 square feet per carton / 39 lbs per carton / 48 cartons per pallet
Warranty:	25 Year Residential

MANNINGTON®

Product Technical Information Sheet – Page 2

Product performance characteristics:

*Abrasion Resistance: Minimum 500 cycles
(ASTM-D4060-90)*

*Finish Adhesion: 5B – 0% removal
(ASTM-D3359-95)*

*Flame spread tunnel test: Meets Class C, flamespread 40
(ASTM E-84)*

*Radiant Panel: Flooring - Greater than or equal to 45 watts /cm², passes NFPA class 1
(ASTM E-648)*

Static Load Limit: 650 PSI(4.5 MPa)

*ADAAG/ADA Meet or Exceed Guideline for Flat Walking Surface(0.6)
(ASTM-D2394)*

Environmental Certifications

LEED EQ 4.1 – If Mannington UltraSpread glue is used – Meets SCAQMD Rule #1168
LEED EQ 4.3 – FloorScore Certified
LEED EQ 4.4 – No added formaldehyde