

MANNINGTON MILLS, INC.
P.O. Box 30
Salem, NJ 08079
(856) 935-3000

To Whom It May Concern:

Benchmark (BM) meets FHA/HUD product requirements. Further information and specification ratings are listed below:

Wear Layer Type	<i>No Wax Vinyl</i>
W/L Thick, Nom., Mills	10 (0.25 mm)
Backing	Fibrous (non-asbestos formulated)
Roll Widths Available	6' (1.83M) 12' (3.66M)
Recommended Use:	
Residential	Yes
Light Commercial	No
Commercial	No
ASTM F-1303 Spec.	Type I, Grade 3, Class A
Weight	2.5 lbs per sq-yd (1.35 kg per sq-m)
ASTM E-648 Critical Radiant Flux Flame Spread CRF>0.45 w/sqcm	Passes as Class 1 Product rating GT 0.45 watts sq/cm
ASTM E-662 NBS Smoke Chamber Test, Smoke Value 450 or less	Passes
Static Load Limit, psi	75
Recommended Grade Level	Above, On and Below Grade
Recommended Adhesive Type	V31 – Full Glue
Recommended Seam Sealer	MSS 20

WARNING:

Do not sand, dry sweep, dry scrape, drill saw, beadblast, or mechanically chip or pulverize existing resilient flooring, backing, lining felt or asphaltic "cut-back" adhesives. These products may contain either asbestos fibers or crystalline silica. Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard. Smoking by individuals exposed to asbestos fibers greatly increases the risk of serious bodily harm. Unless positively certain that the product is non-asbestos containing material, you must presume it contains asbestos. Regulations may require that the material be tested to determine asbestos content. The RFCI's Recommended Work Practices for Removal of Resilient Floor Coverings are a defined set of instructions which should be followed if you must remove existing resilient floor covering structures. You may also refer to Mannington's Professional Installation Handbook (#839168).