

MANNINGTON MILLS, INC.
P.O. Box 30
Salem, NJ 08079
(609) 935-3000

To Whom It May Concern:

Jumpstart™ is manufactured in the U.S.A. and meets FHA/HUD product requirements. Further information and specification ratings are listed below:

Wear Layer Type	Low Gloss Urethane
W/L Thick, Nom., Mills	10 (0.25mm)
Backing	Fibrous (non-asbestos)
Roll Widths Available	6' (1.83M) 12' (3.66M)
Recommended Use:	
Residential	Yes
Light Commercial	No
Commercial	No
ASTM F-1303 Spec.	Type I, Grade 3, Class A
Recycle Content Nom.	4% by weight post consumer 4% by weight post industrial
ASTM E-648 Critical Radiant Flux Flame Spread CRF>0.45 w/sqcm	Class I
ASTM E-662 NBS Smoke Chamber Test, Smoke Value 450 or less	Yes
Static Load Limit, psi	75
Recommended Grade Level	Above, On and Below Grade
Recommended Adhesive Type	V-31
“ ” Spread	Full or Perimeter
Recommended Seam Sealer	MLG 33

WARNING:

Do not sand, dry sweep, dry scrape, drill saw, beadblast, or mechanically chip or pulverize existing resilient flooring, backing, lining felt or asphaltic "cut-back" adhesives. These products may contain either asbestos fibers or crystalline silica. Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard. Smoking by individuals exposed to asbestos fibers greatly increases the risk of serious bodily harm. Unless positively certain that the product is non-asbestos containing material, you must presume it contains asbestos. Regulations may require that the material be tested to determine asbestos content. The RFCI's Recommended Work Practices for Removal of Resilient Floor Coverings are a defined set of instructions which should be followed if you must remove existing resilient floor covering structures; you may also refer to Mannington's Professional Installation Handbook (#839168).