

MANNINGTON®

Product Technical Information Sheet

Product Summary:

Product(s):	TimberPlus®
Thickness:	1/2" Nominal (11.3 mm)
Width:	8" Nominal (206 mm)
Length:	87" Nominal (2200 mm)
Gloss:	Matte (10)
Construction:	3 ply engineered Premium
Face Veneer:	Hardwood White Oak
Face Thickness:	0.6 mm
Origin:	Made in Sweden
Profile:	Micro-Bevel
Installation:	Glue or Float
Packaging:	4 planks per carton / 10.89 lbs (4.94 kg) per plank 19.5 square feet per carton / 44.4 lbs per carton / 48 cartons per pallet
Warranty:	Lifetime Residential / 5 Year Light Commercial

MANNINGTON®

Product Technical Information Sheet – Page 2

Product performance characteristics:

Abrasion Resistance: 5000 cycles w/out breakthrough
(ASTM-D4060-90)

Finish Adhesion:
(ASTM-D3359-95)

Flame spread tunnel test: Class C (Type III)
(ASTM E-84)

Radiant Panel: Class I – 0.45 wt/ cm²
(ASTM E-648)

Static Load Limit:
(4.5 MPa)

ADAAG/ADA
(ASTM-D2394)

Janka Harness: Minimum 1300
(ASTM-D1037)

Smoke Denisty: ≤ 450
(ASTM E662)

Carb Phase 2 Complaint: Yes
(ASTM D6007-14)