

MANNINGTON®

Product Technical Information Sheet

Product Summary:

Product(s):	Kodiak
Width:	Nominal 5" (127mm)
Length:	Random up to 48"(1210 mm); average 70% full length boards per carton
Thickness:	Nominal 3/8" (9.5 mm)
Gloss level:	Matte Gloss – (10 on a 60 degree scale)
Wearlayer:	8 layer polyurethane finish with aluminum oxide and enhanced scratch resistance.
Construction:	5 ply engineered Premium Hardwood –
Face Species:	White Teak (Gmelina arborea)
Face Thickness:	1.5 mm prior to final sanding
Inner Plies:	White Teak (Gmelina arborea)
Origin:	Made in the Guatemala from Mexican raw materials – Lacey act Compliant and plantation grown
Profile:	Full Bevel
Installation:	Full glue, staple, nail, or float
Packaging:	40 square feet per carton / 41.41 lbs per carton / 32 cartons per pallet
Warranty:	25 Year residential warranty

MANNINGTON®

Product Technical Information Sheet – Page 2

Product performance characteristics:

*Abrasion Resistance: Minimum 400 cycles
(ASTM-D4060-90)*

*Finish Adhesion: 4B-5B – 0% removal
(ASTM-D3359-95)*

*Flame spread tunnel test: Meets Class C, flamespread 40
(ASTM E-84)*

*Radiant Panel: Flooring - Greater than or equal to 45 watts /cm², passes NFPA class 1
(ASTM E-648)*

Static Load Limit: 650 PSI(4.5 MPa)

*ADAAG/ADA Meet or Exceed Guideline for Flat Walking Surface(0.6)
(ASTM-D2394)*

*Janka Harness: Minimum 1300
(ASTM-D1037)*