

Fuse table

Book DALI 750 mm

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LCA 35W 150-700MA O4A LP PRE											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	30	38	46	58		18	25	28	35		13,6 A 304μ*

* Input voltage 230V, Time measured at 50% Ipeak

Book DALI 900, 1500, 1800, 2100 & Whiteboard 1500 mm >

Book DALI 2700 & Whiteboard 2000 mm >

ateljé Lyktan

Book DALI 900, 1500, 1800, 2100 mm, Whiteboard 1500 mm

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LCA 50W 100-400MA O4A LP PRE											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	21	28	36	45		13	17	22	27		22,4 A 176µ*

* Input voltage 230V, Time measured at 50% Ipeak

Book DALI 2700 mm, Whiteboard 2000 mm

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LCA 75W 100-400MA O4A LP PRE											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	21	28	35	45		13	17	21	27		23 A 174µ*

* Input voltage 230V, Time measured at 50% Ipeak

Fuse table

Book On/Off 750 mm

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LC 25W 100–500mA flexC Ip EXC											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	35	50	60	76		23	30	36	46		21 A 126μ*

* Input voltage 230V, Time measured at 50% Ipeak

Book On/Off 900, 1500, 1800, 2100 & Whiteboard 1500 mm >

Book On/Off 2700 & Whiteboard 2000 mm >

ateljé Lyktan

Book On/Off 900, 1500, 1800, 2100 mm, Whiteboard 1500 mm

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LC 50W 100–400mA flexC Ip EXC											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	16	21	26	35		10	13	16	21		32 A 240μ*

* Input voltage 230V, Time measured at 50% Ipeak

Book On/Off 2700 mm, Whiteboard 2000 mm

Automatic circuit breaker type:	C10	C13	C16	C20		B10	B13	B16	B20		Inrush current
Driver: LC_75W_100-400mA_flexC_lp_EXC_en											I_{max} time
Installation Ø:	1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		1,5mm ²	1,5mm ²	2,5mm ²	4mm ²		
Number of drivers/fuse:	16	21	26	35		10	13	16	21		30 A 253μ*

* Input voltage 230V, Time measured at 50% Ipeak