

## MESSAGE DISPLAYS

### M5 MESSAGE DISPLAY LED WARNING SIGN

The Message Display has been designed from the ground up, improving upon our already market leading product, using the latest surface mount LEDs, bespoke optics, fully sealed display housing and a new touch screen O-LED control panel.

#### Models

PART NO.	VOLTAGE	COLOUR
CD0012A	10-30	Amber
CD0012R	10-30	Red



O-LED touchscreen controller

#### LED Display Panel features


- Innovative optical design to improve legibility in sunshine
- Support for a single controller to operate multiple displays
- Support for multiple controllers to operate a single display
- Flexible mounting options - auto text rotation for mounting upside-down
- Easily readable from 100 metres
- Multivoltage 10-30V operation
- ECE R10, IP67 (display only), C-Tick
- Temperature Range: -20°C to +65°C
- Warranty: 1 Year
- C3DNA network reduces wiring to the display

#### Controller Features


- O-LED graphic touchscreen display
- MicroSD message storage and firmware
- PC message programmer (Code 3 DNA Toolbox)
- User configurable startup screen
- Adhesive tape mounting or optional swivel-mount option

#### Pursuit™ Lightbar Compatible

- Single cable run to the Pursuit™ lightbar with a message display



Red LED option



Amber LED option