

## Notice of Minor Network Change

---

May 23, 1997  
No. SIA-7d

### Message Waiting Indicator Tone

---

Stentor, on behalf of its Telecommunications Companies, announces a change of the Audible Message Waiting Indication (AMWI), as currently used on the Companies' DMS-100 switches. The change is scheduled to begin by 1Q98.

The AMWI had been previously disclosed in TAPAC Bulletin No. 91-04, dated May 1, 1991. In future, the standard Message Waiting Indicator Tone as defined by Bellcore will be used throughout the Stentor network.

**Compatibility Impact:**

Some terminals that are designed to recognize a message waiting indicator tone may be impacted. The standard message waiting indicator tone reverts to normal steady dial tone after two seconds.

**Documentation:**

The standard Message Waiting Indicator Tone is described in Bellcore Technical Reference TR-NWT-000506, LSSGR LATA Switching Systems Generic Requirements, Signaling, Issue 3, September 1991, Revision 1, November 1991.

---

If you have any questions regarding the above, please contact:

**Stentor Resource Centre Inc.**  
Director - Interface Standards Research  
160 Elgin Street, Room 480  
Ottawa, Ontario, K1G 3J4 Canada

Tel: (in Canada) 1-800-265-6608  
Tel: (Worldwide) (613) 781-6816  
Fax: (613) 781-6454  
e-mail: disclosure@stentor.ca

---