



COMMODORE

WALL MOUNT

**Solutions offered as a boiler
or a volume water heater.**



From easy install to long-lasting reliability, it's the trusted commercial boiler.



Easy installation and maintenance



Compact wall-mounted boilers and water heaters



Low NOx Certified



Robust stainless steel heat exchanger



Practical Full Text Control

EXPERT ACADEMY

Training seminars are offered throughout the year at our state-of-the-art training headquarters in West Deptford, New Jersey and at several locations throughout the United States. Our facility provides classroom and hands-on training in our live fire training room led by our experienced and knowledgeable instructors.



Modulation
up to 6.5:1



Modbus connection
as standard



Field
convertible



Optional BACnet
accessory



Models range from
299 to 500 MBH



Cascade up to
16 boilers



Easy-to-read
error history



As **industry leaders** in the manufacture and supply of quality stainless steel hot water heating equipment, we provide highly dependable and reliable products. We are also committed to providing expert training for contractors and installers to ensure our products deliver long-lasting performance.


Specifications.

COMMODORE WM COMMERCIAL WALL BOILER							
Model	Input MBH		Output* MBH	Net AHRI Rating MBH	AHRI Certified		
	Min	Max			AFUE	Thermal Efficiency	Combustion Efficiency
CB299W	46	299	289	238	95.1%	-	-
CB399W	72	399	381	329	-	95.5%	95.4%
CB470W	83	470	453	394	-	95.6%	95.1%
CB500W	83	500	475	413	-	95.1%	94.5%

*Output is "Heating Capacity" for units with inputs <300 MBH and "Gross Output" for units ≥ 300 MBH.

COMMODORE WWH WALL VOLUME WATER HEATER				
Model	AHRI Certified			GPH 100F Rise
	Input Rate BTU/H	Thermal Efficiency	Input Minimum BTU/H	
WH299W	299,000	96.0%	46,000	346
WH399W	399,999	96.0%	72,000	457
WH470W	470,000	96.0%	83,000	549
WH499W	499,000	96.0%	83,000	583

DIMENSIONS AND SPECIFICATIONS									
Turn Down	Rated Volume	S/R Water Conn. MNPT	Gas Conn. NPT	Flue Conn. Vent/Air	Vent Length	Boiler			Weight lbs
						Height	Width	Depth	
6.5:1	2.1	1-1/2"	1"	4"	200'	33-1/3"	17-1/3"	21-1/5"	184
5.5:1	2.5	1-1/2"	1"	4"	121'	33-1/3"	17-1/3"	21-1/5"	193
5.7:1	2.7	1-1/2"	1"	6"	200'	33-1/3"	17-1/3"	21-1/5"	198
6:1	2.7	1-1/2"	1"	6"	200'	33-1/3"	17-1/3"	21-1/5"	198



NSF/ANSI/CAN 372