



Technical submittal



Products: **Burstock expansion vessel PV25W**

Project:

Customer:

Date:

- ⌚ Floor standing expansion vessel
- ⌚ 25 litres capacity
- ⌚ 10bar max pressure
- ⌚ Nitrogen pre-charged
- ⌚ 1.7bar pre-charge pressure (Heating)
- ⌚ 3.5bar pre-charge pressure (DHW)
- ⌚ WRAS approved
- ⌚ Butyl rubber diaphragm suitable for temperatures of 70°C



Model	Capacity (litres)	Connection size	Max pressure (bar)	Shipping weight (kg)	Pre-charge pressure (bar)		Dimensions			
					Heating	DHW	A	B	C	D
PV25W**	25	G $\frac{3}{4}$ "	10	5	1.7	3.5	280	448	499	N/A

** Wall bracket kit variant available

Model no.	Vessel(s) capacity (litres)	# Max. system volume supported for given vessel capacity (litres)		† Estimated max. installed boiler power for given vessel capacity (kW)	
		Water only	@10% antifreeze	Water only	@10% antifreeze
PV25W**	25	302	266	30	26

Based on 80°C maximum flow temperature and factory pre-sets: Cold fill pressure = 1.8bar, vessel charge pressure = 1.7bar, acceptance volume factor 0.35, expansion factors: water 0.029, antifreeze @10% solution 0.0329.

† Estimated using 1kW of installed power for every 10 litres of system volume. Note that maximum system volume supported by a given vessel capacity is around 12% less for a system using antifreeze @10% solution in water when compared against using water alone.

