

Technical submittal

Products: **Upton UF600-3**

Project:

Customer:

Date:

- ⊗ Aluminium heat exchanger
- ⊗ 15:1 turndown ratio
- ⊗ 6 bar rated heat cell
- ⊗ 5-year heat exchanger warranty
- ⊗ 96.5% gross seasonal efficiency
- ⊗ 545.1kW output @80/60°C
- ⊗ Fits in a footprint of 700 x 940mm
- ⊗ Passes through a standard door width
- ⊗ 33mg/kWh NOx emissions gross (natural gas)
- ⊗ Noise at maximum modulation of 59.7dba
- ⊗ Built-in controls platform with sequence control and capable of controlling up to 16 boiler modules and hot water circuits
- ⊗ British manufactured



	Boiler model	Units	UF600-3
	No. of modules		3
Energy	Building Regulations Part L seasonal efficiency	% gross	96.5
	Building Regulations Part L seasonal efficiency	% nett	107.2
	Boiler output 80/60°C	kW	545.1
	Boiler output 50/30°C	kW	593.7
	Boiler input gross (maximum)	kW	626.6
	Boiler input nett (maximum)	kW	564.2
	Boiler output 80/60°C (minimum)	kW	36.3
	Boiler output 50/30°C (minimum)	kW	39.6
Water	Water content	litres	48.6
	System design flow rate @ 11°C ΔT rise	l/s	13
	Water side pressure loss @ 11°C ΔT rise	mbar	710
	System design flow rate @ 20°C ΔT rise	l/s	7.2
	Water side pressure loss @ 20°C ΔT rise	mbar	217
	Minimum operating water pressure	barg	0.5
	Maximum operating water pressure	barg	5.3
	Maximum water pressure	barg	6
	Maximum flow temperature setting	°C	85
	Minimum flow temperature setting	°C	30
Gas	Gas flow rate (maximum) (Nat gas)	m³/hr	57.3
	Nominal inlet pressure (Nat gas)	mbar	20
	Maximum inlet pressure (Nat gas)	mbar	25
Flue	Approx flue gas volume @ 72°C, 9.0% CO ₂	m³/hr	942
	Maximum flue gas temperature @ 80/60°C	°C	72
	Maximum flue gas temperature @ 50/30°C	°C	42
	Pressure available at flue connection	Pa (mbar)	150 (1.5)
	NO _{x,pond,Hs} (gross) emission (0% excess oxygen, dry air) (Nat gas)	mg/kWh	33
	NO _{x,pond} (nett) emission (0% excess oxygen, dry air) (Nat gas)	mg/kWh	36
	NO _x Class		6
Connection	Water flow/return connections	inches	R2-11
	Gas inlet connection pipe thread size	inches	G1¼
	Flue connection diameter (I/D)	mm	250
	Condensate trap connections (O/D)	mm	34
Electrics	Electrical supply		230V ~ 50Hz
	Power consumption - maximum boiler modulation	W	660
	Run current (per module)	Amp	1
	Approx shipping weight	kg	624
	Noise emission @1m @max modulation (per module)	Max dB (A)	59.7

*Dependent on ΔT - see full brochure







Technical submittal

Products: **Upton UF600-3**

Project:

Customer:

Date:



*Note: Rear clearance required when using Hamworthy pipe kits.

All dimensions in mm unless otherwise stated.