COMMODORE FLOOR STANDING COMMERCIAL BOILERS: CB 1250 & CB 2000

Ideal Heating North America 1240 Forest Parkway, Suite 100, West Deptford, NJ 08066
USA Telephone: 800.411.9999 | **customerservice@idealheatingna.com**

JOB NAME: _____

DATE: _____

LOCATION: _____

ENGINEER: _____

WHOLESALER: _____

MODEL NUMBER: _____

GAS TYPE: _____

CONTRACTOR: _____

CB 1250 Dimensions



COMMODORE FLOOR STANDING COMMERCIAL BOILERS: CB 1250 & CB 2000

CB 2000 Dimensions



Dimensions and Specifications

Product Selection	Model Number	S/R Water Vic. Conn.	Gas Conn. NPT	Flue Conn. Vent/Air	Vent Length	Height	Width	Depth	Weight lbs.
	CB 1250F	2-1/2"	2"	8"/8"	150'	47"	55"	34"	992
	CB 2000F	2-1/2"	2"	8"/8"	115'	47"	68"	34"	1213

Commodore Water Tube Commercial Boiler Performance Data

Product Selection	Model Number	Min Input MBH	Max Input MBH	Output, MBH	Maximum Supply Temp., F	Net AHRI Rating, Water,MBH	Thermal, Efficiency, %	Combustion Efficiency. %
	CB 1250F	156	1250	1200	194	1043	97.0%	96.6%
	CB 2000F	236	2000	1945	194	1691	98.0%	97.0%

COMMODORE FLOOR STANDING COMMERCIAL BOILERS: CB 1250 & CB 2000

Standard Features and Equipment

- Field convertible
- LCD display with easy to use controls
- On/Off Power Switch
- Laptop computer connection
- Supply and Return water temperature sensors
- Integrated pressure sensor
- Flue gas temperature sensor
- Burner door temperature clixon
- Up to 99.0% thermal efficiency
- Full stainless steel heat exchanger
- Premix burner
- Internal automatic air vent with drain connection
- Outdoor model (NEMA 4)
- Condensate trap
- External ignition transformer connection

Boiler and External Controls

- 7-inch graphical colored touchscreen
- Large backlit LCD with full text information programming and errors
- Modbus connection standard
- 0-10 VDC remote flow temperature set point control
- 0-10 VDC remote boiler power output
- Bacnet module for remote access available

Data Logging

- Real time and date clock
- Days of operation
- Successful ignition attempts
- Ignition failures
- Flame failures
- Up to 48 readable lockout errors
- Hours since last service
- Hours until next service
- Total days of boiler operation

ideal HEATING NORTH AMERICA

COMMODORE FLOOR STANDING COMMERCIAL BOILERS: CB 1250 & CB 2000

Low Voltage Connections

- Outdoor temperature sensor
- System temperature sensor
- DHW temperature sensor
- Modbus
- Cascade connection
- On/Off thermostat or OpenTherm
- 0-10V VDC input
- Flow switch DHW
- PWM pump control
- External low water cut off
- Gas pressure switch
- Universal safety contact set 1 & 2

Cascade

- Integrated cascade control
- Cascade control of up to 16 boilers
- Remote operation and heat demand indication from each boiler
- Four cascade power program modes
- Boiler sequencing and rotation control
- Following boilers fully operational on failure of lead boiler

High Voltage Connections

- Boiler pump
- System pump
- DHW pump
- DHW twv (3-way valve)
- Alarm

Additional Features

- Two level frost protection
- Short cycle protection
- Adjustable minimum & maximum power
- Temperature boost function
- Multiple levels of security
- PWM control for variable speed pumps
- Domestic hot water priority time control
- Selectable priority for domestic hot water or heating

Accessories

☐	External flow temperature sensor
☐	Indirect tank temperature sensor
☐	PC software+interface cable for programming boiler
☐	BACNET module
☐	0-10V Modulating circulator signal converter
☐	Low water cutoff
☐	Fixed speed high efficiency circulator
☐	Fixed speed standard efficiency circulator
☐	Variable speed high efficiency circulator
☐	75 psi relief valve (3/4" & 1" & 1-1/4" & 1-1/2")
☐	100 psi relief valve (3/4" & 1" & 1-1/4")
☐	125 psi relief valve (3/4" & 1" & 1-1/4")
☐	150 psi relief valve (3/4" & 1" & 1-1/4")
☐	8"/ 10"/ 12" Motorized Flue Damper
☐	Neutralizer 400MBH - 7000MBH

ASME H

AHRI CERTIFIED

GAS-FIRED c UL us LISTED

idealheatingna.com

©2025 Ideal Heating NA Technical Information subject to change without notice.