BRAZED PLATE XCHANGER

900kW










Brazed Plate Heat Exchanger – 900kW



900kW is the nominal capacity of the plate heat exchanger applying the operating conditions shown below. Please contact Hamworthy Heating to confirm the expected performance if the operating conditions differ from those shown.

DN100



Installed dimensions

Dimension	Α	В	С	D	E
DN100	330	866	500	120	888

Installed weight (including PHE, spools and support)

DN100 Kit = 127.5kg

	UNITS	HOT SIDE	COLD SIDE	
Mass flow rate	kg/s	10.8	10.8	
Inlet temperature	°C	80	50	
Outlet temperature	°C	60	70	
Pressure drop	kPa	14.1	19.4	
Heat exchanged	kW	900		
Heat transfer area	m²	21.7		
Flow configuration		Countercurrent		
Number of plates / thickness		88 / 0.3 mm		
Number of passes		1	1	
Pressure vessel code		PED		
Design pressure at 90.00 Celsius	Bar	19	19	
Design pressure at 225.0 Celsius	Bar	15	15	
Design temperature	°C	-196.0 / 225.0		
Volume	L	28.0	17.9	

Standard materials

Cover plates	Stainless steel
Connections	Stainless steel
Plates	Stainless steel
Brazing	Copper

PLEASE NOTE

The plate heat exchangers are to be used for system separation only. They must not be used for the direct production of domestic hot water.

They should not be used for direct heating of swimming pool water where the chlorinated pool water would pass directly through the plate heat exchanger.

Connections

FRAME & HEADER

Stratton mk3	DN50	DN80	DN100
			V
System			
DN100			
Flanged			
PN16	<u> </u>	<u> </u>	

