

Pennzoil Ultra Platinum™ Full Synthetic Motor Oil					
Specifications:	0W-20	5W-20	5W-30	10W-30	0W-40
API SN	X	X	X	X	X
SM	X	X	X	X	X
SL	X	X	X	X	X
SJ	X	X	X	X	X
ILSAC GF-5	X	X	X	X	
ACEA A1/B1-10, A1/B1-12	X	X	X	X*	
ACEA A5/B5-10, A5/B5-12			X	X*	
Chrysler MS 6395 (SE011)	X	X	X	X	
Chrysler MS 12633 (SRT) (SE049)					X
Ford WSS-M2C930-A (SE015)		X			
Ford WSS-M2C945-A (SE018)		X			
Ford WSS-M2C929-A			X		
Ford WSS-M2C946-A (SE019)			X		
Ford WSS-M2C947-A (SE051)	X				
GM 6094M (SE023)		X	X	X	
GM 4718M (Corvette, Cadillac) (SE022)			X	X	
GM dexos1® (SE020)	X	X	X		
HONDA/ACURA HTO-06 (SE002)			X		
Volvo			X		

Pennzoil Platinum® Full Synthetic Motor Oil				
Specifications:	0W-20	5W-20	5W-30	10W-30
API SN	X	X	X	X
SM	X	X	X	X
SL	X	X	X	X
SJ	X	X	X	X
ILSAC GF-5	X	X	X	X
ACEA A1/B1-10, A1/B1-12			X	
ACEA A5/B5-10, A5/B5-12			X	
Chrysler MS 6395 (SE011)	X	X	X	X
Ford WSS-M2C930-A (SE015)		X		
Ford WSS-M2C945-A (SE018)		X		
Ford WSS-M2C929-A			X	
Ford WSS-M2C946-A (SE019)			X	
Ford WSS-M2C947-A (SE051)	X			
GM 6094M (SE023)		X	X	X
GM 4718M (Corvette, Cadillac) (SE022)			X	X
GM dexos1® (SE020)	X	X	X	
HONDA/ACURA HTO-06 (SE002)			X	
Volvo			X	

Pennzoil Platinum® Euro Full Synthetic Motor Oil					
	Euro Motor Oil	Euro Motor Oil	Euro Motor Oil	Euro L Motor Oil	Euro LX Motor Oil
Specifications:	0W-40	5W-30	5W-40	5W-30	0W-30
API SN	X	X**	X	X	X
SL		X			
CF	X	X	X		
ACEA A3/B3-12	X	X	X		
ACEA A3/B4-12	X	X	X		
ACEA C2					X
ACEA C3				X	X
BMW LL-01 (SE007)		X	X		
BMW LL-04 (SE008)				X	
Chrysler MS 10725 (SE009)			X		
Chrysler MS 10850			X		
Chrysler MS 11106 (SE010)				X	
Chrysler MS-12991 (SE050)			X		
Ferrari			X		
Maserati			X		
Fiat 9.55535.Z2	X	X	X		
Fiat 9.55535.M2	X	X	X		
Fiat 9.55535.DS1					X
Fiat 9.55535.GS1					X
GM dexos2® (SE021)				X	
Mercedes-Benz 229.3 (SE028)	X	X	X		
Mercedes-Benz 229.31 (SE029)				X	X
Mercedes-Benz 229.5 (SE030)	X	X	X		
Mercedes-Benz 229.51 (SE031)				X	X
Mercedes-Benz 229.52					X
Mercedes-Benz 226.5	X	X	X		
Porsche A40 (SE033)	X		X		
Porsche C30 (SE034)					X
PSA B71 2296			X		
VW 502 00 (SE003)	X	X	X		
VW 505 00 (SE045)	X	X	X		
VW 504 00 (SE004)					X
VW 507 00 (SE006)					X
Renault RN0700	X	X	X		
Renault RN0710	X	X	X		

Pennzoil Gold™ /Synthetic Blend Motor Oil				
Specifications:	0W-20	5W-20	5W-30	10W-30
API SN	X	X	X	X
SM	X	X	X	X
SL	X	X	X	X
SJ	X	X	X	X
ILSAC GF-5	X	X	X	X
Chrysler MS 6395 (SE011)	X	X	X	X
Ford WSS-M2C930-A (SE015)		X		
Ford WSS-M2C945-A (SE018)		X		
Ford WSS-M2C929-A			X	
Ford WSS-M2C946-A (SE019)			X	
Ford WSS-M2C947-A (SE051)	X			
GM 6094M (SE023)		X	X	X
GM dexos1® (SE020)	X	X	X	

Pennzoil® Racing Motor Oil		
	Pennzoil Platinum® Racing	Pennzoil® GT Performance Racing
Specifications:	10W-60	25W-50
API SN	X	
SM	X	
SL	X	
SJ	X	X
CF	X	
ACEA A3/B3-12	X	
ACEA A3/B4-12	X	
Ferrari	X	
Maserati	X	
Mercedes-Benz 229.1	X	
VW 501 01/505 00 (SE045)	X	

Pennzoil Platinum® High Mileage Vehicle® Motor Oil (US only)		
Specifications:	5W-20	5W-30
API SN	X	X
SM	X	X
SL	X	X
SJ	X	X

Pennzoil® High Mileage Vehicle® Motor Oil					
Specifications:	5W-20	5W-30	10W-30	10W-40	25W-60†
API SN	X	X	X	X	
SL					X
SJ					X

* Engine protection only
 ** Meets Engine Test Requirements
 Beginning with its 2011 model year vehicles, GM began recommending oils meeting the GM dexos1® oil performance level for all gasoline engine vehicles. Pennzoil Platinum® 5W-30 Full Synthetic Motor Oil exceeds GM dexos1® specifications.

These charts are to be used as a guideline only. Please refer to your individual vehicle owner's manual for proper viscosity grade and specification of oil to use.

† Available for export only.

Pennzoil® Euro AV SAE 5W-30 Full Synthetic Motor Oil

Specifications:	ACEA C3	VW 502 00	VW 505 00	VW 505 01
Euro AV Motor Oil	X	X	X	X

These charts are to be used as a guideline only. Please refer to your individual vehicle owner's manual for proper viscosity grade and specification of oil to use.

Pennzoil® Conventional Motor Oil

Specifications:	5W-20	5W-30	10W-30	10W-40	20W-50	30	40
API SN	X	X	X	X	X	X	X
SM	X	X	X	X	X	X	X
SL	X	X	X	X	X	X	X
SJ	X	X	X	X	X	X	X
ILSAC GF-5	X	X	X				
Chrysler MS 6395 (SE011)	X	X	X				
Ford WSS-M2C930-A (SE015)	X						
Ford WSS-M2C945-A (SE018)	X						
Ford WSS-M2C929-A		X					
Ford WSS-M2C946-A (SE019)		X					
GM 6094M (SE023)	X	X	X				

Pennzoil® Marine & Motorcycle Engine Oils and Gear Lubricants*	SAE GRADE	GL-5	SH	JASO MA	TC-W TC-W2 TC-W3	TC
Pennzoil Marine® Premium Plus 2-Cycle Oil					X	X
Pennzoil Marine® XLF Synthetic Blend 2-Cycle Oil					X	X
Pennzoil® Premium Outboard and Multi-Purpose 2-Cycle Oil					X	X
Pennzoil Marine® High Viscosity Lower Unit Gear Lube	80W-90	X				

* For a complete listing of Pennzoil® engine oils, visit www.pennzoil.com for products and specifications

Pennzoil® Lubricants	Description	Product Keys Applicable to Each Product
Pennzoil Platinum® LV Multi-Vehicle ATF	Synthetic, Multi-Vehicle ATF with GM DEXRON®-VI and Ford MERCON® LV service fill approval. Suitable for many other transmissions. ¹	AD, AF3, AF6, MLV, TIV, WS, AF2, AP4, BTF, FA, GA, MA, MA5, MSP, MA5S, SL001/002/04/006/014/016/017/024/025/027/030/036/040/042/043/044/046/049/050/054/059/060/061/062/064/065/067/072/077/080/081/082/090/092/094/097/098/099/100/101/102/106/107/108/111/117/119/129/130/142/143/144/153
Pennzoil Platinum® High Mileage ATF	Synthetic, Multi-Vehicle ATF for GM DEXRON®-III, Ford MERCON® V/MERCON®, Toyota T-IV (JWS-3309), and other higher viscosity ATF requirements. ¹	AF2, AF3, MA, MA5, MA5S, TIV, TTA, SL002/004/021/024/025/027/028/030/038/040/042/045/053/060/061/062/064/065/067/080/081/082/089/092/097/098/100/101/103/119/129
Pennzoil Platinum® ATF+4	Chrysler approved, synthetic ATF for Chrysler ATF+4® and Type 7176 applications. ¹	AP4
Pennzoil Platinum® CVT-2	Nissan, Honda, Suzuki and other CVT applications. ²	VTF04, VTF06, VTF07, VTF08, VTF11, VTF13, VTF14, VTF16, VTF17, VTF18, VTF19
Pennzoil Platinum® Axle 75W-90	Full synthetic, API GL-5 axle and gear oil. ³	GL-5EP
Pennzoil Platinum® Axle 75W-140	Full synthetic, API GL-5 axle and gear oil. ³	GL-5EP
Pennzoil Platinum® Gear 75W-90 (GL-4)	Full synthetic, API GL-4 axle and gear oil.	GL-4
Pennzoil® Dex/Merc ATF	GM DEXRON®-III(H), Ford MERCON® and Allison C-4 ATF. ¹	AF2, AF3, MA, SL028/045/053/080/129
Pennzoil® Axle 80W-90	Mineral oil SAE 80W-90, API GL-5 axle and gear oil with limited slip. ³	GL-5 EP
Pennzoil® Synchromesh	Manual Transmission Fluid	GLS42, GLS43
Pennzoil® ATF Type F	ATF specifically designed for Ford Type F applications.	FA, GA

¹ Not for use in CVT or Ford Type F applications unless specifically allowed against a listed oil code.

² CVT Fluids are typically unique in characteristics, check application before use of any fluid.

³ Pennzoil® axle oils contain limited slip friction modifier for many applications. Higher performance loads requiring more than 3-4% limited slip friction modifier requires use of additional friction modifier supplement.

KEY TO LUBRICANTS

General

No Pennzoil® product for CTF, CV, MLV, MSP, RO, Synthetic VTF, WS, VTA

■ Contact the Pennzoil® Technical Services Department at 1-800-237-8645, opt. 4 & 2 Monday through Friday, 8:00am to 5:00pm Central Time.

* Product with limited-slip additive.

ATF+4® is a registered trademark of Chrysler LLC

DEXRON® is a registered trademark of General Motors Corporation

MERCON® is a registered trademark of Ford Motor Company

AE - Pennzoil Platinum® LV multi-vehicle ATF/Contact Technical Services
 AP4 - Suitable for use for vehicles requiring ATF+4®
 BC - Pennzoil® Bar and Chain Oil
 BL - C.T.S.q
 BTF - C.T.S.q
 AF6 - Meets specifications of DEXRON®-VI
 AF3 - Suitable for use for vehicles requiring DEXRON®-III
 LB, BJ - Pennzoil® Premium Wheel Bearing 707L Red Grease
 LM, LS - Pennzoil® Premium Wheel Bearing 707L Red Grease
 FA - Ford Type F ATF
 GLS - Obtain OEM Part Number at End of Application Listing and C.T.S.q

GM P/N 12345349 - Pennzoil Platinum® Axle 75W-90 (APIGL-5)
 GM P/N 12345577 - Pennzoil® Synchromesh Manual Transmission Fluid
 GM P/N 1052931 - Pennzoil® Conventional SAE 5W-30
 GM P/N 1237826 - Pennzoil® Synthetic 75W-90 GL-5
 Dodge P/N 4874464 - Pennzoil Synchromesh Manual Transmission Fluid
 HB - Heavy Duty Brake Fluid DOT 3 Heavy Duty Brake Fluid DOT 3/ DOT 4
 HBH - C.T.S.q
 HG - C.T.S.q
 MA - Suitable for use for vehicles requiring MERCON®
 MA5 - Suitable for use for vehicles requiring MERCON® V

MO - Motor oil, any API Service Classification
 MT-1 - API MT-1 Manual Transmission Fluid Specification (SEO - C.T.S.q See motor oil key or contact Technical Services
 SLF - C.T.S.q Contact Technical Services
 SLG - C.T.S.q Contact Technical Services
 SLS - C.T.S.q Contact Technical Services
 SP - C.T.S.q Contact Technical Services
 TU - C.T.S.q Contact Technical Services
 GL-2 - C.T.S.q Contact Technical Services
 GL-3 - C.T.S.q Contact Technical Services
 TIV - Toyota Type IV and Aisin JWS 3309 applications in GM, Ford, Mini, Saab, Volvo and others
 TO-4 - Caterpillar TO-4 Transmission Fluid Specification