


RIDGELINE™
AUTOMOTIVE
DEX-COOL® COMPATIBLE
ANTIFREEZE/COOLANT
PRODUCT DESCRIPTION

RIDGELINE™ DEX-COOL® COMPATIBLE ANTIFREEZE/COOLANT is a premium Organic Acid Technology (OAT), virgin ethylene glycol-based fluid. Specially formulated with industry-leading additives, this product provides optimum performance in vehicles requiring DEX-COOL®* (GM 6277M or GMW 3420) coolant.

APPLICATIONS

- Provides up to 5 years or 150,000 miles of protection
- Full Organic Acid Technology (OAT)
- Helps prevent freeze-ups and boil-overs
- Meets or exceeds ASTM D3306 and SAE J1043 specifications, additional specifications on the back

FEATURES AND BENEFITS

- Premium quality, extended life coolant
- Free of phosphates, borates, nitrites, silicates, and amines
- Protects against corrosion of all cooling system metals, including aluminum
- Provides freeze and boil-over protection
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Formulated for use in newer Chrysler® (2013 and later), Ford® (2011 and later), and GM® (1996 and later) vehicles requiring an orange OAT coolant
- Compatible with major American brands of extended life Organic Acid Technology type antifreeze/coolant formulated to meet the DEX-COOL®* requirement (GM 6277M or GMW 3420)

**DEX-COOL® is a registered trademark of the General Motors Corporation®. Consult your vehicle's owner's manual for recommendations. Chrysler®, Ford®, and GM® are registered trademarks of their respective corporations.*



Distributed by:
Parkland Corporation
 1800, 240 4 Ave SW, Calgary, AB T2P 4H4

™ Trademark of Parkland Corporation
www.ridgelinelubricants.com
ridgeline.information@parklandusa.com



RECOMMENDED FOR USE IN

RIDGELINE™ DEX-COOL® COMPATIBLE ANTIFREEZE/COOLANT

ASTM D3306	Ford WSS-M97B44-D/D2	GMW 3420	SAE J1034
ASTM D4985*	Ford WSS-M97B44-E1/E2	John Deere JDM H24C	VW TL774-C/F
Chrysler MS-12106	Ford WSS-M97B55-A	John Deere JDS-G135	
Chrysler MS-90032	GM 6277M (DEX-COOL®)**		

*Meets performance requirements; chemical requirements not applicable to OAT coolants. Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures.
**DEX-COOL® is a registered trademark of the General Motors Corporation*. Chrysler®, Ford®, GM®, John Deere®, and Volkswagen® are registered trademarks of their respective corporations.

TYPICAL PROPERTIES

TECHNICAL INFORMATION	CONCENTRATE	50/50 RTU
Fluid Color	Orange	Orange
Density @ 68°F (20°C), lb/gal	9.3	8.9
pH (50v% solution)	8.1	8.1
Coolant Lifetime, miles (years)	150,000 (5,000)	150,000 (5,000)

FREEZE/BOIL PROTECTION CHART <small>¹Using a 15 psi pressure cap</small>	% Cooling System Capacity	PROTECTION FROM	
		Freezing Down To	Boiling Up To ¹
	40	-13° F	+260° F
	50	-34° F	+265° F
	60	-62° F	+270° F

SHIPPING INFORMATION	DRUMS
Package Quantity	55 Gallons
Package Dimensions	23.5" x 34.5"
Gross Container Weight - Concentrate	≈547 Pounds
Gross Container Weight - 50/50	≈527 Pounds
Gross Weight on Pallet - Concentrate	≈2251 Pounds
Gross Weight on Pallet - 50/50	≈2169 Pounds
Quantity Per Pallet	4
Pallet Dimensions	48" x 48" x 39.4"
Product Part Number - Concentrate	RIDDEXORG100
Product Part Number - 50/50	RIDDEXORG50
UPC Code - Concentrate	652138111334
UPC Code - 50/50	652138111341
Weight Per Gallon - Concentrate	≈9.3 Pounds
Weight Per Gallon - 50/50	≈8.9 Pounds

 **WARNING: REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV.**

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category.
Parkland Fuel Corporation takes no responsibility for product misuse or misapplication.

Distributed by:
Parkland Corporation
1800, 240 4 Ave SW, Calgary, AB T2P 4H4
™ Trademark of Parkland Corporation
www.ridgelinelubricants.com
ridgeline.information@parklandusa.com

