

Flexible Duct - Firebreak Duct R1.0

Polyaire Firebreak Flexible Duct is manufactured from metalised Mylar and clear Mylar substrates, incorporating totally enclosed helically wound galvanised high tensile steel wire.

The layers are bonded with a fire retardant adhesive to ensure long life in all ambient conditions.

The insulation is a polyester thermal blanket manufactured to rigid standards.



Item Code	Diameter (mm)
120001/6	Ø 150
120003/6	Ø 200
120005/6	Ø 250

Application

- Steam return lines
- Insulation in ventilation and air supply systems
- Air conditioning systems
- Thermic insulation in order to prevent heat loss or loss of cold
- Preventing of condensation in ventilation systems

Specifications

Temperature range	-20 °C to +80 °C
Operating pressure	-190pa to +1200Pa
Standard diameter range	150 - 250 mm
Standard length	6 meters

Features

Metalised Inner Core

Polyester Insulation

Metalised Outer Fire Jacket

General Use: Heating and cooling for do Alu/poly laminate

Classifications

AS 4254 (Test Certificates available)

Please contact our Sales Office on for selection guidance on the above:

3-4 Torridge Close,
Telford Way Industrial Estate,
Kettering, Northants, NN16 8PY

P 01536 519 922

E sales@polyaire.co.uk