

## TITANIUM DIOXIDE PLANT, TERENGGANU

# GEOTUBE® dewatering and containment of gypsum wastes



<b>Industry:</b>	Mining
<b>Application:</b>	Waste management
<b>Location:</b>	Malaysia
<b>Product:</b>	<b>GEOTUBE®</b>

## Overview

Industrial waste, often in slurry form and containing contaminants, needs to be managed and disposed of properly to protect the environment. This case study focuses on the dewatering of gypsum waste slurry at a titanium pigment plant in Malaysia using geotextile tubes. The plant produces titanium pigments through a process that involves treating ilmenite with sulfuric acid, resulting in the discharge of red gypsum waste in slurry form with a solid concentration of approximately 16%. Initially, the waste was treated using filter presses (Figure 1).

## Challenge

The plant faced capacity and storage issues as the filter presses were operating at maximum capacity, and the sludge lagoons were full. The high cost of adding more filter presses and the low return on investment led the plant to seek more affordable dewatering alternatives.

## Solution

To address the problem, the client explored the option of installing **GEOTUBE®** dewatering units suggested by specialist engineers from Solmax as part of an integrated plant processing solution.

A Rapid Dewatering Test (RDT) or Jar Test was conducted to determine the appropriate polymer type and dosage needed to flocculate the sludge. The results confirmed the correct dosage and the effectiveness of **GEOTUBE®** GT500D fabrics in containing and dewatering the red gypsum slurry. The discharge produced visually clear and high-quality effluent. The results were further validated through a **GEOTUBE®** Dewatering Test or Pillow Bag test. Additionally, a full-scale pilot tube was utilized, employing **GEOTUBE®** GT500D fabric with dimensions of 8.8 m (29 ft) circumference and 27.5 m (90 ft) length. This pilot confirmed a 39% dewatered solids concentration and identified operational implications and actual solid volumes within the tube.

**A GEOTUBE® solution was successfully implemented at a titanium dioxide plant in Malaysia to dewater gypsum waste slurry. This approach resolved capacity and storage challenges, while improving dewatering efficiency and reducing processing costs.**

## CASE STUDY

### GEOTUBE® dewatering and containment of gypsum wastes



Figure 1

Over the course of a year, more than 100 units of **GEOTUBE®** dewatering tubes, with dimensions of 36.6 m (120 ft) 1 circumference and lengths ranging from 57 m (187 ft) to 43.8 m (143 ft), were installed as part of an integrated plant waste capture program. These tubes captured a total of 180,000 m<sup>3</sup> (235,710 yd<sup>3</sup>) of dry solids. The use of **GEOTUBE®** dewatering tubes resulted in cost savings in terms of capital expenditure and reduced overall maintenance and operational costs.

Before deployment, the positions of the **GEOTUBE®** units were marked on the geomembrane liner. Each unit, weighing approximately 1.3 tons (2,866 pounds), was lifted and positioned using a mobile crane. The units were then manually unrolled and unfolded by operators or with the assistance of a mechanical winch attached to a 4WD vehicle. A 100 mm

(3.9 in) diameter flexible hose was used to connect the slurry main pipe to the **GEOTUBE®** dewatering units. The filling ports of each unit were connected with flexible hoses, and the slurry inflow for each port was regulated by a gate valve installed between the main slurry pipe and the flexible hose.

## Result

**GEOTUBE®** dewatering technology increased the plant's dewatering capacity by approximately 25%, allowing it to meet the sudden surge in demand for titanium dioxide. Furthermore, the plant was able to conduct a complete maintenance overhaul of its aging mechanical dewatering equipment without disrupting production.



Solmax is not a design or engineering professional and has not performed any such design services to determine if Solmax's goods comply with any project plans or specifications, or with the application or use of Solmax's goods to any particular system, project, purpose, installation, or specification.

Products mentioned are registered trademarks of Solmax in many countries of the world.