







- Product Depth 13.75" (349 mm)
- AC Power Input 120VAC 60 Hz & 230VAC 50 Hz version available

**3- Mixer (2)** (މިކްޝަރު 2 ޖަނަވަރުގެ ޖަދުވަލުގައި ބަޔާންކޮށްފައިވާ ގޮތަށް)

- 10-Channel Mixing Console
- Max. 6 Mic / 12 Line Inputs (4 mono + 4 stereo)
- 2 GROUP Buses + 1 Stereo Bus
- 2 AUX (incl. FX)
- "D-PRE" mic preamps with an inverted Darlington circuit
- 1-Knob compressors
- High-grade effects: SPX with 24 programs
- 24-bit / 192kHz 2in / 2out USB Audio functions
- Works with the iPad (2 or later) through the Apple iPad Camera Connection Kit / Lightning to USB Camera Adapter
- Includes Cubase AI DAW software download version
- PAD switch on mono inputs
- +48V phantom power
- XLR balanced outputs
- Internal universal power supply for world-wide use
- Optional Rack Mount Kit RK-MG12 Available
- Metal chassis
- Dimensions(W×H×D): 308 mm x 118 mm x 422 mm (12.1" x 4.6" x 16.6")
- Net Weight: 4.2 kg (9.3 lbs.)

**4- Loud (6)** (ލޯޑް 6 ޖަނަވަރުގެ ޖަދުވަލުގައި ބަޔާންކޮށްފައިވާ ގޮތަށް)

- Applicable Drivers TU-632, TU-632M, TU-652, TU-652M
- Sound Pressure Level 110 dB (1 W, 1 m) (When operated with a driver.)
- Frequency Response 200 Hz - 6,000 Hz (When operated with a driver.)
- Dust/Water Protection IP65 (When operated with a driver.)
- Driver Coupling 1 - 3/8 18 threads (inch screw)
- Operating Temperature -20 °C to +55 °C (must be free from dew condensation)
- Finish Horn flare and flange: Aluminum, White, powder coating
- Reflector horn: HIPS, White
- Bracket: Steel, White, powder coating
- Screws and bolts: Stainless steel
- Dimensions  $\Phi 500 \times 357$  (D) mm
- Weight 2.7 kg













