

TCR SERIES | 250 TO 500 KG MINI AIR HOISTS



**RED ROOSTER
LIFTING**

RAISING EXPECTATIONS

The **TCR-MINI** is a chain hoist from Red Rooster Lifting. This is part of our air hoist hook suspension range for lifting equipment applications in industry. Compact and lightweight.



The **Red Rooster Lifting** TCR series of air hoists offers a comprehensive range of lifting equipment suited to all types of industrial and marine environments. Red Rooster Lifting hoists are the perfect lifting solution for where the duty is high, or where a robust hoist is required to withstand harsh conditions. The hoists comply with the UK supply of Machinery (Safety) Regulations 2008 and the European Machinery Directive. The hoists can be UKCA marked or CE marked.

STANDARD FEATURES

- Compact and lightweight body
- Toku rotary vane motor
- Robust epicycle gearbox
- Failsafe automatic internal disc brake
- Mechanical upper & lower switches
- Aluminium housing
- Internal silencing down to 83 dB(A)
- Alloy safety swivel hooks with safety catch
- Load chain 4 x 12mm of European manufacture to EN818-7

AVAILABLE OPTIONS

- Marine specification
- Special paint systems
- Corrosion protection
- UK Ex scheme or ATEX zone 1 specification
- Chain collectors (PVC, galvanised or stainless steel)
- Air service units
- Radio control
- Main air shut off valve



**UK EX SCHEME ZONE 2
ATEX ZONE 2
AS STANDARD**

T: +44 (0) 1651 872101
sales@redroosterlifting.com

REDROOSTERLIFTING.COM

Red Rooster Lifting Limited Nauta House, The Meadows, Oldmeldrum, Inverurie, Aberdeenshire, UK, AB51 0EZ




TCR SERIES | 250 TO 500 KG MINI AIR HOISTS

**RED ROOSTER
LIFTING**

RAISING EXPECTATIONS

DIMENSIONS

All measurements are in mm
Information subject to change without notice



| MODEL | A | B | C | D | E | F | G | HØ | I | J |
|-----------|-----|-----|----|----|-----|-----|----|----|----|----|
| TCR-250 | 310 | 111 | 37 | 74 | 112 | 140 | 15 | 35 | 22 | 20 |
| TCR-500/2 | 360 | 118 | 35 | 83 | 112 | 140 | 15 | 36 | 22 | 20 |

| MODEL | WLL | CHAIN FALLS | LIFTING SPEED WITH LOAD | LIFTING SPEED WITHOUT LOAD | LOWERING SPEED WITH LOAD |
|-----------|--------|-------------|-------------------------|----------------------------|--------------------------|
| TCR-250 | 250 kg | 1 | 9.3 m/min | 19.0 m/min | 17.9 m/min |
| TCR-500/2 | 500 kg | 2 | 4.6 m/min | 9.5 m/min | 9.0 m/min |

| MODEL | MIN HOSE DIA | AIR CONNECTION | AIR CONSUMPTION LIFTING | AIR CONSUMPTION LOWERING |
|-----------|--------------|----------------|-------------------------|--------------------------|
| TCR-250 | 1/2" HOSE | 1/2" BSP | 13 l/sec | 15 l/sec |
| TCR-500/2 | 1/2" HOSE | 1/2" BSP | 13 l/sec | 15 l/sec |

| MODEL | WORKING PRESSURE | WEIGHT WITH 3M HOL | ADDITIONAL METRE HOL | G.A. DRAWING |
|-----------|------------------|--------------------|----------------------|--------------|
| TCR-250 | 6 bar | 7.0 kg | 0.35 kg | 1368-00 |
| TCR-500/2 | 6 bar | 9.0 kg | 0.7 kg | 1368-01 |