

CRESCENT

Di-16

Cost Effective 16x1 HDMI 1.4 input Multiviewer



Key Features

- Low latency - single frame processing delay
- Low power consumption - only uses 40W
- Accepts 16 HDMI 1.4 inputs
- Accepts 4 LPCM channels audio inputs
- Windows can be sized and moved freely
- Decodes up to 4 embedded audio per HDMI input
- Total of 64 audio meters
- 2 simultaneous and identical HDMI and SDI outputs
- Output resolution up to 1080P@60Hz
- Ethernet for configuration and external control
- Dynamic UMD/Label and Tallies (TSL)
- Standalone labels and 2 customizable logos
- 2 digital and 2 analog clocks can be synced with LTC or NTP
- 32 GPIs for tallies, count up/down triggers or preset recalls
- Borders can be turned on or off
- 2 sets of safe area markers
- Visual alarm tags for format, video/audio presence
- Audio monitoring outputs - stereo, AES, SDI or HDMI
- 1 RU with optional redundant power supply
- Optional redundant power supply
- 3 year limited warranty

Accessories

Standard

- Rack-mounts
- 16 x Type D to A HDMI cables
- 4x RJ50 to DB9 cables for GPI
- 4x breakout terminal blocks
- RJ45 to DB9 cable for serial (RS-232)


Optional

- RPS-12VDC60W-
 - Redundant power supply
- Di-BOP
 - HDMI A to HDMI D Connector plate

CRESCENT

Di-16

Rear View



Di-BOP - HDMI A to HDMI D CONNECTOR BREAKOUT PLATE

Specifications

Model	Di-16
Description	16 input HDMI 1.4 multiviewer with advanced on-screen display (OSD)
Inputs	16 x HDMI (1080i/P, 720P, 576i, 480i, 50/59.95/60Hz), 4 LPCM channels of audio
Output	2 identical HDMI 1.4 with 2 x 3G SDI outputs
On Screen Displays	Borders, labels (4 per window), fonts, tally LED, analog and digital clocks, logos, UMD, OMD, IMD
Max Resolution	1080P@60Hz
Power	AC 90 to 240V with optional DC redundant power supply
Power Consumption	70W
Environment	Operating temperature: 0 ~ 45 C
	Operating humidity: 20 ~ 90% RH
	Storage temperature: -20 ~ 60 C
EMI/RFI	Complies with FCC Part 15 Class A, CE, EU, EMC, C-tick
Dimension	1RU. 446 x 452 x 87 mm (L x W x H)
Weight	8.6 kg