

## SUPERCAT 7 *Performance Grade CAT7 cable*

The SoundTools SuperCAT 7 cable is designed with the same diameter, durability and flexibility as our professional grade SoundTools SuperCAT cable, while also enhancing the shielding and crosstalk rejection. SuperCAT 7 is ready to deliver the most demanding digital audio and data signals while remaining easy to coil. Built for live touring or installation applications, SuperCAT 7 meets specifications for CAT7.



Durable and abrasion-resistant thanks to a robust polyurethane halogen-free jacket, and capable of handling extreme temperatures ranging from -20/+60°C -4/+140°F, SuperCAT 7 is ready for the toughest indoor or outdoor environments.

The SuperCAT 7 features four foil-shielded and precisely-twisted pairs with 26/7 AWG stranded wire. When combined with SoundTools Audio Over CAT products, SuperCAT 7 allows for optimal transmission of analog XLR, DMX, COM, and AES3 signals with up to four balanced lines on a single cable.

### SUPERCAT 7 SPECIFICATIONS

**Conductor:** 26/7 AWG

**Jacket:** Halogen-free LSZH - PUR & flame retardant

**Copper:** oxygen free copper

**Shield:** tinned copper wire braid

**AES / EBU Digital Impedance:** 110 Ω

**Impedance:** 100Ω

**Temp:** -20°C/-4°F to 60°C/140°F

**Outer Diameter:** 6.5 mm (same diameter as SuperCAT)

**Shielding:** S/FTP

**Shielding factor:** 100%

**Max Pull:** 80 N (17.98 lbf)

**Capacitance core/core:** 44 pF/m

**Propagation velocity (approx.):** 77%

**Delay skew:** 10 ns @ 100 MHz/100 m

**Bandwidth:** up to 10Gbp/s @ 600MHz



AES72 compliant (SoundTools products use the AES72-20 standard)