

# Spirent **fX3 HSE Modules**

## Quint-Speed High-Speed Ethernet Test Modules


The Spirent fX3 family of multi-speed High-Speed Ethernet (HSE) test modules are the industry's first capable of quint-speed operation. Support for the latest Data Center speeds of 25G and 50G are combined with "legacy" speeds of 100G, 40G and 10G to ensure dataplane QoS performance over realistic routing and cloud infrastructure topologies of the latest high-density multi-terabit routers and cloud-scale Data Center switches.

The Spirent fX3 Ethernet multi-speed test modules combine Spirent's industry-leading Layer 2-3 traffic generation and analysis with powerful network emulation and application layer protocols for emulating a wide range of device types, users and protocols. These modules deliver the highest performance per dollar for Layer 2-7 testing. Reduced power consumption and quint-speed support results in lower CAPEX and OPEX. These modules are ideal for functional and performance testing of data center and service provider network infrastructure where extreme protocol performance is not required.

These modules are designed with two QSFP28 ports that utilize four 25G electrical lanes each to support the latest 100/50/25G transceivers and interconnects. The multi-speed QSFP28 interfaces are combined with Spirent's flexible FPGA logic to allow mode-switching of the fX3 packet generation and analysis engine to operate at 100, 50, 40, 25 and 10 gig speeds. The fX3 module family is available in several speed combinations to match your test needs and budget.

### Applications

- **Service Provider Core and Edge Routers**—Verify scale, reliability, and performance of Layer 2 & 3 services including IP data and video delivered via unicast routing, multicast routing, switching, Multicast VPN, EVPN and MPLS VPN technologies.
- **Data Center Top of Rack, Spine and Core Switches**—Benchmark capacity of high-density and capacity fabrics using IETF RFC 2544, RFC 2889 and RFC 3918 methodologies with easy test setup using dynamically bound traffic and automated wizards.
- **Carrier Ethernet**—Verify scale, reliability, performance of Ethernet services delivered via Ethernet OAM (CFM IEEE 802.1ag and Y.1731), MPLS-TP, VPLS, PWE3 Pseudowires, bridged Ethernet, packet transport protocols or combinations of these technologies.



# Spirent fX3 HSE Modules

## Quint-Speed High-Speed Ethernet Test Modules

### Features & Benefits

- Quint- and tri-speed versions provide flexibility for validating multi-speed switches and line cards. 100G-only versions also available to fit your budget needs
- Enable and disable Clause 74 BASE-R FEC, Clause 91 RS-FEC, and Clause 108 RS-FEC
- QSFP28 connector form-factor supports the latest 4x25G-based transceivers
- Low total cost of ownership compared to other test modules in its class:
  - Excellent price-performance ratio that delivers faster time-to-market by combining leading-edge technical innovation with Spirent's extensive testing experience
  - Intelligent power control to shut down unused test modules and allows faster boot time to bring capacity back on-line quickly
  - More total throughput than the competition for a given power footprint
  - Enhanced chassis software license value—Two to four times the device or end-user emulation per chassis with no increase in software costs
  - Topology emulation lowers Capex by eliminating the need for multiple DUTs in multiprotocol tests
  - Intelligent results gets answers in a fraction of the test time required by competitive products
  - Faster boot and firmware upgrade times mean less downtime in continuous running 24x7 regression test beds
- Spirent TestCenter's industry-leading Layer 2-3 feature set:
  - "Hardened" system proven for testing from a single port up to 2,100 ports
  - Stress ASIC and backplane designs with live traffic changes.  
The number of emulated devices, the traffic they emanate and the rate at which they send it can all be changed "on the fly" making for more realistic tests and faster troubleshooting
  - Best-in-industry for measuring ultra-low sub-microsecond latencies with 2.5ns precision and resolution. Latency accuracy up to 10 times better than the competition
  - 19 different scheduling algorithms available for finding the right traffic to emulate the real world or tax the device's ability to handle any traffic pattern—from micro-bursts to carefully timed sequences of "killer" frames
- fX3 modules support Spirent TestCenter's deep analysis system:
  - Port counts, rates, errors and protocol summaries provide a high-level view for quick drilldown to specific issues
  - Broadest set of per stream metrics with simultaneous control and data plane results allows most tests to be run in a single pass
  - Real-time traffic filters allow analysis down to specific fields. Multiple metrics can be simultaneously collected and instantly analyzed
  - Dynamic views feature multi-metric extraction, sorting and operation in real-time or post-test
  - Full packet capture enables timing, sequencing and content analysis for individual packets
  - Powerful filters ensure the capture buffer is filled with relevant data

### Technical Specifications

Spirent fX3 Module				
Maximum support	Speed	Maximum ports per slot	Maximum ports per SPT-N12U chassis	Maximum ports per SPT-N4U chassis
FX3-100GO-T2	100G Only	2	24	4
FX3-100GD-T2	100G/25G	2/8	24/96	4/16
FX3-100GTN-T2	100G/50G/25G	2/4/8	24/48/96	4/8/16
FX3-100GTL-T2	100G/40G/10G	2/2/8	24/24/96	4/4/16
FX3-100GQ-T2	100G/50G/40G/25G/10G	2/4/2/8/8	24/48/24/96/96	4/8/4/16/16
FX3-25GD-T2	25G/10G	8/8	96/96	16/16

## Spirent fX3 Module

Port density	2-port QSFP28 module
Media support and FEC options See accessory table below for part numbers*	<p>Support varies by module speed mode</p> <ul style="list-style-type: none"> <li>• 100G: 100GBASE-SR4, 100GBASE-CR4, 100GBASE-LR4, plus additional MSA PMDs</li> <li>• 50G: 25/50G Consortium 50GBASE-CR2,</li> <li>• 40G: 40GBASE-SR4, 40GBASE-CR4, 40GBASE-LR4</li> <li>• 25G: 802.3by 25GBASE-CR, 25GBASE-CRS, 25GBASE-SR</li> <li>• 10G: 10GBASE-SR, 10G Copper DAC</li> <li>• QSFP28 to SFP28 breakout cable options</li> <li>• Auto-Negotiation and Link Training for 100G, 50G, 40G and 25G</li> <li>• Clause 74 BASE-R FEC, Clause 91 RS-FEC, and Clause 108 RS-FEC</li> <li>• 25/50G Consortium 50GBase-R FEC CL74, 25/50G Consortium 50GBase RS-FEC CL91</li> <li>• IEEE 25GBASE CR CL74, CL108, CR-S CL74, SR FEC CL108</li> <li>• 25/50G Consortium 25GBase-R FEC CL74, 25/50G Consortium 25GBase RS-FEC CL91</li> </ul>
Line clocking and packet time stamping (modules get their transmit line clocking and time-stamping from the control modules on the SPT-N12U and SPT-N4U)	<ul style="list-style-type: none"> <li>• Stratum-3 rated oscillator is the default time source</li> <li>• Frame time stamp resolution of 2.5ns</li> <li>• GPS and CDMA-based external time sources are supported</li> <li>• IEEE 1588v2 and NTP packet-based external time sources are supported</li> <li>• TIA/EIA-95B-based external time sources are supported</li> </ul>
Inter-module and Inter-chassis Time Synchronization	<p>Ports in the same chassis are locked to the internal timing source. For separate systems:</p> <ul style="list-style-type: none"> <li>• Timing chain synchronization with +/- 20ns accuracy</li> <li>• Synchronized via GPS or CDMA network</li> <li>• Using NTP or PTP packet-based approaches (requires supporting controller version)</li> </ul>
User reservation	Per-port reservation
Transmit / receive streams per port	TX/ 64K TX and RX/128K for all speeds
VFDs and Variable Fields	<ul style="list-style-type: none"> <li>• 6 VFDs available for each 2048 (100G/40G) and 512 (25G/10G) stream templates</li> <li>• 8m route insertion table entries in 100G/40G modes and 4m in 25G/10G mode</li> </ul>
Scheduler Mode Support	<ul style="list-style-type: none"> <li>• Port Based - traffic scheduling handled at the port level</li> <li>• Rate Based - key parameters determined at the port level with division among the individual stream blocks</li> <li>• Priority Based - scheduling determined at the stream block level using user-assigned priorities. Precise scheduling of CBR and bursty traffic for QoS testing</li> <li>• Manual Mode - manual control of stream sequence</li> </ul>
Frame length range and controls	100% line rate for frames of 64-16383 bytes controlled by fixed, increment, decrement, random and IMIX modes
Statistics	<ul style="list-style-type: none"> <li>• Nearly 50 transmit stats per port reported in real time. Includes L1-4 counters and rates and checksum and CRC errors</li> <li>• Over 40 real-time measurements per stream including advanced sequencing, latency, jitter and data integrity</li> </ul>
Transmit clock adjustment	+/- 100 PPM in 1 PPM increments for each 100G port or each QSFP28 interface for 50G, 40G, 25G and 10G
Capture	<ul style="list-style-type: none"> <li>• 2GB per 100G or 40G port</li> <li>• 1GB per 50G port</li> <li>• 512MB per 25G port</li> <li>• Capture software includes sophisticated trigger and filtering controls</li> </ul>
Histograms	Port-level histogram modes for latency, jitter, interarrival time, frame length, sequence run length and sequence difference check
Operating temperature	15° C - 35° C, 20% - 80% RH (non-condensing)

## Spirent fX3 HSE Modules

### Quint-Speed High-Speed Ethernet Test Modules



#### Spirent TestCenter Protocol Emulation

Spirent TestCenter protocols available as separately licensed packages. Below is a sample list of supported protocols. Contact Spirent for a full list of capabilities and packages.

Enterprise and data center switch protocol support	<ul style="list-style-type: none"><li>OpenFlow 1.3 / 1.0: OpenFlow switch and controller emulation testing</li><li>Routing, multicast and bridging: All major IPv4 and IPv6 unicast and multicast routing protocols, IGMPv1/v2/v3, MLDv1/v2, LACP, STP, RSTP and MSTP</li><li>Data center: VXLAN, EVPN, DCBX, FCoE, FIP, 802.1Qbb</li><li>Stateful L4-7: HTTP, SIP, FTP, and LACP and LAG emulation</li></ul>
Service Provider protocol support	<ul style="list-style-type: none"><li>WAN SDN: PCE-P, BGP-LS (Link State), BGP Flow Spec and Segment Routing for ISIS, OSPF and BGP</li><li>NFV: Validate performance and scale for NFVI and VNFs including vSwitch, BGP v RouteReflector, vBNG, vCPE and vRouter</li><li>Routing and MPLS: All major IPv4 and IPv6 unicast and multicast routing protocols, RSVP-TE, LDP, VPLS-LDP, VPLS-BGP, BGP/MPLS-VPN, EVPN (RFC 7432), PBB EVPN, mVPN, NG MVPN, GTM, BFD, MPLS BFD, LSP Ping, TWAMP and PWE3 (RFC4447)</li><li>Access: ANCP, PPPoE, DHCP, L2TP, L2TPv3, IGMPv1/v2/v3, MLDv1/v2, DHCP-PD and PPPoEv6</li><li>Carrier Ethernet and bridging: LACP, STP, RSTP, MSTP, 802.1ag CFM, Y.1731, PBB, PBB-TE, Link OAM</li><li>Stateful L4-7: HTTP, SIP, FTP, Unicast/Multicast RTSP, RAW TCP, and LACP and LAG emulation</li><li>Mobile Backhaul: MPLS-TP, 1588v2 and Synchronous Ethernet</li></ul>

## Ordering Information

#### Test Modules

Description	Part Number
SPIRENT FX3 100GBE ONLY QSFP28 2-PORTS	FX3-100GO-T2
SPIRENT FX3 100 25GBE QSFP28 2-PORT	FX3-100GD-T2
SPIRENT FX3 25 10GBE QSFP28 2-PORT	FX3-25GD-T2
SPIRENT FX3 100 40 10GBE QSFP28 2-PORT	FX3-100GTL-T2
SPIRENT FX3 100 50 25GBE QSFP28 2-PORT	FX3-100GTN-T2
SPIRENT FX3 100 50 40 25 10GBE QSFP28 2-PORT	FX3-100GQ-T2
SPIRENT FX3 10GBE ONLY QSFP28 8-PORT	FX3-10GO-T2
SPIRENT FX3 40GBE ONLY QSFP28 2-PORT	FX3-40GO-T2
SPIRENT FX3 50GBE ONLY QSFP28 4-PORT	FX3-50GO-T2

#### Accessories for QSFP28 interfaces

Optical transceiver QSFP28 100GBASE-SR4 MMF 850NM	ACC-6095A
Optical Transceiver QSFP28 100GBASE-LR4 SMF 1310NM	ACC-6096A
Copper DAC QSFP28 100GBASE-CR4 1M	ACC-1034A
Copper DAC QSFP28 100GBASE-CR4 3M	ACC-1035A
Copper DAC QSFP28 100GBASE-CR4 5M	ACC-1038A
Active Optical Cable (AOC) QSFP28, 5M	ACC-1036A

## Contact Us

For more information, call your Spirent sales representative or visit us on the web at [www.spirent.com/ContactSpirent](http://www.spirent.com/ContactSpirent).

[www.spirent.com](http://www.spirent.com)

© 2020 Spirent Communications, Inc. All of the company names and/or brand names and/or product names and/or logos referred to in this document, in particular the name "Spirent" and its logo device, are either registered trademarks or trademarks pending registration in accordance with relevant national laws. All rights reserved. Specifications subject to change without notice.

Americas 1-800-SPIRENT  
+1-800-774-7368 | [sales@spirent.com](mailto:sales@spirent.com)

US Government & Defense  
[info@spirentfederal.com](mailto:info@spirentfederal.com) | [spirentfederal.com](http://spirentfederal.com)

Europe and the Middle East  
+44 (0) 1293 767979 | [emeainfo@spirent.com](mailto:emeainfo@spirent.com)

Asia and the Pacific  
+86-10-8518-2539 | [salesasia@spirent.com](mailto:salesasia@spirent.com)