


Promo Scrape Impressions

→ LOGO MAT • OUTDOOR & INDOOR



→ WHY CHOOSE THIS MAT?

Promo Scraper Impressions feature your custom logo or artwork on nylon fibers.

- Unique blend of nylon fibres provides **superior scraping** action against dirt and debris
- High-quality dyes offer brilliant **colour fastness** and **image durability**
- Strong rubber backing provides maximum durability in **high traffic** applications
- In-house designers for a **quick** turnaround time
- **Drainage holes** available for sizes up to 130 x 200 cm
- Fully launderable
- The textiles used are **OEKO-TEX® certified**, ensuring they meet stringent standards for safety and environmental responsibility

→ SPECIFICATIONS

- Yarn** ECONYL® Regenerated Nylon
1/8th gauge cut pile
Mat weight: 3.9 kg/m²
- Backing**
- **Primary backing:** Non woven spun bonded polyester
 - **Rubber backing:** 100% nitrile rubber with up to 34% post-industrial recycled content in the polymer - phthalate free - For maximum oil resistance, durability, and performance. Compression-molded with reinforced borders on all four sides.
 - **Pattern:** Claw
 - **Thickness:** 3 mm
 - **Drainage holes (optional):** Ø 7mm
- Border**
- **Width:** 20 mm
 - **Thickness:** 2,5 mm
 - Available with and without rubber border
- Other properties**
- **Pile weight:** 715 g/m²
 - **Pile height:** 7 mm
 - **Stitch rate:** 6 spi
 - **Total weight:** 3,9 kg/m²
 - **Water retention:** 3.160 kg/m²
 - **Flammability:** C-fl

Size Tolerance: +/- 2% -
Weight Tolerance: +/- 5%



→ COLOURS

A1		B8		D5	
A2		B9		D6	
A3		B10		D7	
A4		C1		D8	
A5		C2		D9	
A6		C3		D10	
A7		C4		E1	
A8		C5		E2	
A9		C6		E3	
A10		C7		E4	
B1		C8		E5	
B2		C9		E6	
B3		C10		E7	
B4		D1		E8	
B5		D2		E9	
B6		D3		E10	
B7		D4			

→ STANDARD SIZES

* No drainage holes Only

60x85	85x300*	115x240*	150x250*
75x85	115x180	115x250*	150x300*
85x115	115x200	200x200*	200x300*
85x150	115x300*	150x200*	
85x240*	115x200*	150x240*	

→ SPECIAL SIZES

No drainage holes – Max. size: 220 cm x 600 cm
With drainage holes – Max. size: 130 cm x 200 cm

→ CLEANING INSTRUCTIONS



1. Pre-wash	2-3 mins	Medium	Cold
2. Drain	1 min		
3. Pre-wash ¹	2-3 mins	Medium	Cold
4. Drain	1 min		
5. Main wash ²	5-8 mins	High	40-50 °C
6. Drain	1 min		
7. Rinse 1	2 mins	High	Cold
8. Drain	1 min		
9. Rinse 2	2 mins	High	Cold
10. Drain	1 min		
11. Extract ³	8-10 mins		

Notes

1. Optional

2. A neutral (pH 7) nonionic detergent is recommended for printed mats. The use of Alkaline built products is not recommended.

3. When extracting perforated mats a single high speed extraction is recommended (maximum G Force 600G). If non perforated mats or mixed loads of perforated mats are being extracted then a split extraction cycle, as below, is recommended to achieve optimum water extraction.

4. Due to the abrasive nature of the pile, the logo scraper mat may attract lint if washed with other mat types, it is therefore recommended that logo scraper mats are not mixed with other mat types during washing. If however mixed products are washed together, to minimise the linting, the mats should be tumble dried.

Split Extraction Cycle and Drying



1. Extract	2 mins	Low speed
2. Drain	1 min	Wash Speed
3. Extract	5 mins	High speed



1. Dry	10-15 mins	Max. 80°C
2. Cool down	5 mins	

Notes

Lay mats flat following removal from dryer. Allow mats to cool before rolling. Roll mats pile out for delivery. Never store printed mats folded or layed pile to pile when damp, to avoid colour transfer.